

Package ‘GWASExactHW’

October 12, 2022

Type Package

Title Exact Hardy-Weinburg testing for Genome Wide Association Studies

Version 1.01

Date 2013-01-04

Author Ian Painter, University of Washington

Maintainer Ian Painter <ipainter@u.washington.edu>

Description This package contains a function to do exact Hardy-Weinburg testing (using Fisher's test) for SNP genotypes as typically obtained in a Genome Wide Association Study (GWAS).

License GPL-3

LazyLoad yes

Repository CRAN

Date/Publication 2013-01-05 08:54:06

NeedsCompilation yes

R topics documented:

GWASExactHW-package	1
HWExact	2

Index	4
--------------	----------

GWASExactHW-package *Exact Hardy-Weinburg testing for Genome Wide Association Studies*

Description

This package contains a function to do exact Hardy-Weinburg testing (using Fisher's test) over all or a selection of SNP genotypes as typically obtained in a Genome Wide Association Study (GWAS).

Details

Package: GWASExactHW
Type: Package
Version: 1.01
Date: 2013-01-04
License: GNU
LazyLoad: yes

The function HWExact runs fast Hardy-Weinberg testing for a set of bi-allelic genotypes.

Author(s)

Ian Painter, University of Washington
Maintainer: Ian Painter <ipainter@u.washington.edu>

References

Wigginton, JE, Cutler, DJ, and Abecasis, GR (2005) A Note on Exact Tests of Hardy-Weinberg Equilibrium. *American Journal of Human Genetics*. 76

HWExact

Function to calculate Hardy-Weinberg exact p-values

Description

This function calculates Hardy-Weinberg (Fisher's) exact p-values for GWAS SNP data.

Usage

```
HWExact(GenotypeCounts)
```

Arguments

`GenotypeCounts` A dataframe of genotype counts, with columns called nAA, nAa and naa, one row for each SNP.

Value

A vector of exact p-values.

Note

This function uses a C function `SNPHWE.c` written by Jan Wigginton as described in the above reference.

Author(s)

Ian Painter

References

Wigginton, JE, Cutler, DJ, and Abecasis, GR (2005) A Note on Exact Tests of Hardy-Weinberg Equilibrium. *American Journal of Human Genetics*. 76

Examples

```
pA<- runif(1)
pAA<- pA^2
pAa<- 2*pA*(1-pA)
paa<- (1-pA)^2

counts<- rmultinom(1000, 3000, c(pAA, pAa, paa) )
genotypes<- data.frame(nAA = counts[1,], nAa = counts[2,], naa = counts[3,])
hwPvalues<- HWExact(genotypes)
```

Index

* **htest**

HWExact, [2](#)

* **package**

GWSExactHW-package, [1](#)

GWSExactHW (GWSExactHW-package), [1](#)

GWSExactHW-package, [1](#)

HWExact, [2](#)