

Package ‘antaresEditObject’

December 21, 2018

Type Package

Title Edit an 'Antares' Simulation

Version 0.1.5

Description Edit an 'Antares' simulation before running it : create new areas, links, thermal clusters or binding constraints or edit existing ones. Update 'Antares' general & optimization settings.

'Antares' is an open source power system generator, more information available here : <<https://antares-simulator.org/>>.

License GPL (>= 2) | file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Depends antaresRead

Imports assertthat, grDevices, data.table, whisker

Suggests testthat, covr

NeedsCompilation no

Author Frederic Breant [aut, cre],
Victor Perrier [aut],
Baptiste Seguinot [ctb],
Benoit Thieurmel [ctb],
Titouan Robert [ctb],
Jalal-Edine Zawam [ctb],
RTE [cph]

Maintainer Frederic Breant <frederic.breant@rte-france.com>

Repository CRAN

Date/Publication 2018-12-21 15:40:03 UTC

R topics documented:

backupStudy	2
checkRemovedArea	3

createArea	4
createBindingConstraint	5
createCluster	6
createDistrict	8
createDSR	9
createLink	10
createPSP	12
createStudy	13
dicoGeneralSettings	14
dicoOptimizationSettings	15
editCluster	15
editLink	16
filteringOptions	18
getPlaylist	19
nodalOptimizationOptions	19
propertiesLinkOptions	20
readIniFile	21
removeArea	21
removeBindingConstraint	22
removeCluster	22
removeLink	23
runSimulation	24
runTsGenerator	24
scenario-builder	25
setPlaylist	27
setSolverPath	28
updateGeneralSettings	28
updateOptimizationSettings	30
writeIni	32
Index	33

backupStudy	<i>Create a backup with an Antares Study</i>
-------------	--

Description

Save an Antares Study or only inputs in a .tar.gz file

Usage

```
backupStudy(backupfile, what = c("input", "study"),
  opts = antaresRead::simOptions())
```

Arguments

backupfile	Name of the backup, without extension. If missing, either the name of the study or 'input' according argument what.
what	Which folder to save, input for the input folder or study for the whole study.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

The path of the backup

Examples

```
## Not run:
backupStudy()

## End(Not run)
```

checkRemovedArea	<i>Seek for a removed area</i>
------------------	--------------------------------

Description

Check if it remains trace of a deleted area in the input folder

Usage

```
checkRemovedArea(area, all_files = TRUE,
  opts = antaresRead::simOptions())
```

Arguments

area	An area
all_files	Check files in study directory.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

a named list with two elements

Examples

```
## Not run:
checkRemovedArea("myarea")

## End(Not run)
```

`createArea`*Create An Area In An Antares Study*

Description

Create An Area In An Antares Study

Usage

```
createArea(name, color = grDevices::rgb(230, 108, 44, max = 255),
  localization = c(0, 0),
  nodalOptimization = nodalOptimizationOptions(),
  filtering = filteringOptions(), overwrite = FALSE,
  opts = antaresRead::simOptions())
```

Arguments

<code>name</code>	Name of the area as a character, without punctuation except - and _.
<code>color</code>	Color of the node
<code>localization</code>	Localization on the map
<code>nodalOptimization</code>	Nodal optimization parameters
<code>filtering</code>	Filtering parameters
<code>overwrite</code>	Overwrite the area if already exist
<code>opts</code>	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:

createArea("fictive_area")

## End(Not run)
```

```
createBindingConstraint
```

Create a Binding Constraint

Description

Create a Binding Constraint

Usage

```
createBindingConstraint(name, id = tolower(name), values = NULL,
  enabled = TRUE, timeStep = c("hourly", "daily", "weekly"),
  operator = c("both", "equal", "greater", "less"),
  coefficients = NULL, overwrite = FALSE,
  opts = antaresRead::simOptions())
```

Arguments

name	The name for the binding constraint
id	An id
values	Values used by the constraint. It contains one line per time step and three columns "less", "greater" and "equal".
enabled	Logical, is the constraint enabled ?
timeStep	Time step the constraint applies to : hourly, daily or weekly
operator	Type of constraint: equality, inequality on one side or both sides.
coefficients	A named vector containing the coefficients used by the constraint.
overwrite	If the constraint already exist, overwrite the previous value.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
createBindingConstraint(
  name = "myconstraint",
  values = matrix(data = rep(0, 8760 * 3), ncol = 3),
  enabled = FALSE,
  timeStep = "hourly",
  operator = "both",
  coefficients = c("fr%myarea" = 1)
)

## End(Not run)
```

createCluster	<i>Create a thermal cluster</i>
---------------	---------------------------------

Description

Create a thermal cluster

Usage

```
createCluster(area, cluster_name, ..., time_series = NULL,
              prepro_data = NULL, prepro_modulation = NULL, add_prefix = TRUE,
              overwrite = FALSE, opts = antaresRead::simOptions())
```

Arguments

area	The area where to create the cluster.
cluster_name	cluster name.
...	Parameters to write in the Ini file. Careful! Some parameters must be set as integers to avoid warnings in Antares, for example, to set unitcount, you'll have to use unitcount = 1L.
time_series	the "ready-made" 8760-hour time-series available for simulation purposes.
prepro_data	Pre-process data, a data.frame or matrix, default is a matrix with 365 rows and 6 columns.
prepro_modulation	Pre-process modulation, a data.frame or matrix, if specified, must have 8760 rows and 1 or 4 columns.
add_prefix	If TRUE, cluster_name will be prefixed by area name.
overwrite	Logical, overwrite the cluster or not.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:

library(antaresRead)
library(antaresEditObject)

# Create a cluster :
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  group = "other",
```

```
    unitcount = 1L, # or as.integer(1)
    `marginal-cost` = 50
  )
# by default, cluster name is prefixed
# by the area name
levels(readClusterDesc())$cluster
# > "fr_my_cluster"

# To prevent this, use `add_prefix`
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  add_prefix = FALSE,
  group = "other",
  `marginal-cost` = 50
)
levels(readClusterDesc())$cluster
# > "my_cluster"

# Pre-process data :

#E this is the default data :
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  prepro_data = matrix(
    data = c(rep(1, times = 365 * 2),
             rep(0, times = 365 * 4)),
    ncol = 6
  )
)

# with a data.frame
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  prepro_data = data.frame(
    v1 = rep(7, 365), # column name doesn't matter
    v2 = rep(27, 365),
    v3 = rep(0.05, 365),
    v4 = rep(0.12, 365),
    v5 = rep(0, 365),
    v6 = rep(1, 365)
  )
)

# Pre-process modulation :
# this is the default data
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
```

```

prepro_modulation = = matrix(
  data = c(rep(1, times = 365 * 24 * 3),
           rep(0, times = 365 * 24 * 1)),
  ncol = 4
)
)

# with a data.frame
createCluster(
  area = "fr",
  cluster_name = "my_cluster",
  prepro_modulation = data.frame(
    var1 = rep(0, 8760), # column name doesn't matter
    var2 = rep(1, 8760),
    var3 = rep(0, 8760),
    var4 = rep(1, 8760)
  )
)

## End(Not run)

```

createDistrict

Create a district

Description

Allows selecting a set of areas so as to bundle them together in a "district".

Usage

```

createDistrict(name, caption = NULL, comments = NULL,
  apply_filter = "none", add_area = NULL, remove_area = NULL,
  output = FALSE, overwrite = FALSE,
  opts = antaresRead::simOptions())

```

Arguments

name	District's name.
caption	Caption for the district.
comments	Comments for the district.
apply_filter	Possible values are add-all to add all areas to the district, remove-all to clear the district, or none (default) to don't apply a filter.
add_area	Character vector of area(s) to add to the district.
remove_area	Character vector of area(s) to remove from the district.
output	Logical, compute the results for the district or not?
overwrite	Logical, should the district be overwritten if already exist?
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
createDistrict(name = "mydistrict",
              apply_filter = "add-all",
              remove_area = c("fr", "be"))

## End(Not run)
```

createDSR	<i>Create a Demand Side Response (DSR)</i>
-----------	--

Description

Create a Demand Side Response (DSR)

Usage

```
createDSR(areasAndDSRParam = NULL, spinning = 2, overwrite = FALSE,
          opts = antaresRead::simOptions())
```

```
getCapacityDSR(area = NULL, opts = antaresRead::simOptions())
```

```
editDSR(area = NULL, unit = NULL, nominalCapacity = NULL,
         marginalCost = NULL, spinning = NULL,
         opts = antaresRead::simOptions())
```

Arguments

areasAndDSRParam	A data.frame with 4 columns area, unit, nominalCapacity, marginalCost and hour. Hour represent the number of activation hours for the DSR per day.
spinning	DSR spinning
overwrite	Overwrite the DSR plant if already exist. This will overwrite the previous area and links.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath
area	an area where to edit the DSR
unit	DSR unit number
nominalCapacity	DSR nominalCapacity
marginalCost	DSR marginalCost

Value

createDSR() and editDSR() returns an updated list containing various information about the simulation.

getCapacityDSR() returns DSR capacity (unit * nominalCapacity of virtual cluster) of the area

Examples

```
## Not run:

library(antaresEditObject)
path<-pathToYourStudy
opts<-setSimulationPath(path, simulation = "input")
area, unit, nominalCapacity and marginalCost
dsrData<-data.frame(area = c("a", "b"), unit = c(10,20),
                    nominalCapacity = c(100, 120), marginalCost = c(52, 65), hour = c(3, 7))

createDSR(dsrData)

createDSR(dsrData, spinning = 3, overwrite = TRUE)
getAreas()

## End(Not run)
## Not run:

getCapacityDSR("a")
editDSR("a", unit = 50, nominalCapacity = 8000)
getCapacityDSR("a")

## End(Not run)
## Not run:

getCapacityDSR("a")
editDSR("a", unit = 50, nominalCapacity = 8000, marginalCost = 45, hour = 9)
getCapacityDSR("a")

## End(Not run)
```

createLink

Create a link between two areas

Description

Create a link between two areas

Usage

```
createLink(from, to, propertiesLink = propertiesLinkOptions(),
  dataLink = NULL, overwrite = FALSE,
  opts = antaresRead::simOptions())
```

Arguments

from	The first area from which to create a link
to	The second one
propertiesLink	a named list containing the link properties, e.g. hurdles-cost or transmission-capacities for example.
dataLink	a matrix with five column corresponding to : trans. capacity (direct) trans. capacity (indirect), impedances, hurdles cost (direct), hurdles cost (indirect). If NULL (default), a matrix whose rows are equal to 1, 1, 0, 0, 0 is set. See Details
overwrite	Logical, overwrite the previous between the two areas if exist
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Details

The five times-series are:

- "NTC direct"the upstream-to-downstream capacity, in MW
- "NTC indirect"the downstream-to-upstream capacity, in MW
- "Impedances"virtual impedances that are used in economy simulations to give a physical meaning to raw outputs, when no binding constraints have been defined to enforce Kirchhoff's laws.
- "Hurdle cost direct"an upstream-to-downstream transmission fee, in euro/MWh
- "Hurdle cost indirect"a downstream-to-upstream transmission fee, in euro/MWh

Value

An updated list containing various information about the simulation.

Note

In Antares, areas are sorted in alphabetical order to establish links between. For example, link between "fr" and "be" will appear under "be". So the areas are sorted before creating the link between them, and dataLink is rearranged to match the new order.

Examples

```
## Not run:
createLink(from = "myarea", to = "myarea2")

## End(Not run)
```

 createPSP

Create a Pumped Storage Power plant (PSP)

Description

Create a Pumped Storage Power plant (PSP)

Usage

```
createPSP(areasAndCapacities = NULL, namePumping = "Psp_In",
  nameTurbinning = "Psp_Out", hurdleCost = 5e-04,
  timeStepBindConstraint = "weekly", efficiency = NULL,
  overwrite = FALSE, opts = antaresRead::simOptions())

getCapacityPSP(area = NULL, nameTurbinning = "Psp_Out",
  timeStepBindConstraint = "weekly", opts = antaresRead::simOptions())

editPSP(area = NULL, capacity = NULL, namePumping = "Psp_In",
  nameTurbinning = "Psp_Out", timeStepBindConstraint = "weekly",
  hurdleCost = 5e-04, opts = antaresRead::simOptions())
```

Arguments

areasAndCapacities	A data.frame with 2 columns installedCapacity and area
namePumping	The name of the pumping area
nameTurbinning	The name of the turbinning area
hurdleCost	The cost of the PSP
timeStepBindConstraint	Time step for the binding constraint : daily or weekly
efficiency	The efficiency of the PSP
overwrite	Overwrite the Pumped Storage Power plant if already exist. This will overwrite the previous area and links.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath
area	an area name
capacity	PSP capacity for the area

Value

createPSP() and editPSP() returns an updated list containing various information about the simulation.

getCapacityPSP() returns PSP capacity of the area

Examples

```

## Not run:

library(antaresEditObject)
path<-pathToYourStudy
opts<-setSimulationPath(path, simulation = "input")
pspData<-data.frame(area=c("a", "b"), installedCapacity=c(800,900))

createPSP(pspData, efficiency = 0.8)

createPSP(pspData, efficiency = 0.66, overwrite = TRUE)
createPSP(pspData, efficiency = 0.98, timeStepBindConstraint = "daily")
getAreas()

## End(Not run)

## Not run:

getCapacityPSP("a")
editPSP("a", capacity = 8000, hurdleCost = 0.1)
getCapacityPSP("a")

areaName<-"suisse"
createArea(areaName, overwrite = TRUE)
pspData<-data.frame(area=c(areaName), installedCapacity=c(9856))
createPSP(pspData, efficiency = 0.5, overwrite = TRUE, timeStepBindConstraint = "daily")

getCapacityPSP(areaName, timeStepBindConstraint = "daily")

## End(Not run)

```

createStudy	<i>Create an empty Antares study</i>
-------------	--------------------------------------

Description

Create an empty Antares study

Usage

```
createStudy(path, study_name = "my_study", antares_version = "6.0.0")
```

Arguments

path	Path where to create study, it should be an empty directory, if it doesn't exist, it'll be created.
------	---

study_name Name of the study.
antares_version Antares number version.

Value

logical vector indicating success or failure

Examples

```
## Not run:  
  
createStudy("path/to/simulation")  
  
## End(Not run)
```

dicoGeneralSettings *Correspondence between arguments of updateGeneralSettings and actual Antares parameters.*

Description

Correspondence between arguments of updateGeneralSettings and actual Antares parameters.

Usage

```
dicoGeneralSettings(arg)
```

Arguments

arg An argument from function updateGeneralSettings.

Value

The corresponding Antares general parameter.

Examples

```
dicoGeneralSettings("year.by.year") # "year-by-year"
```

dicoOptimizationSettings
*Correspondence between arguments of
updateOptimizationSettings and actual Antares parameters.*

Description

Correspondence between arguments of updateOptimizationSettings and actual Antares parameters.

Usage

```
dicoOptimizationSettings(arg)
```

Arguments

arg An argument from function updateOptimizationSettings.

Value

The corresponding Antares general parameter.

Examples

```
dicoGeneralSettings("year.by.year") # "year-by-year"
```

editCluster *Edit an existing cluster*

Description

Edit an existing cluster

Usage

```
editCluster(area, cluster_name, ..., time_series = NULL,  
prepro_data = NULL, prepro_modulation = NULL, add_prefix = TRUE,  
opts = antaresRead::simOptions())
```

Arguments

area	The area where to create the cluster.
cluster_name	cluster name.
...	Parameters to write in the Ini file.
time_series	the "ready-made" 8760-hour time-series available for simulation purposes.
prepro_data	Pre-process data, a data.frame or matrix, default is a matrix with 365 rows and 6 columns.
prepro_modulation	Pre-process modulation, a data.frame or matrix, if specified, must have 8760 rows and 1 or 4 columns.
add_prefix	If TRUE, cluster_name will be prefixed by area name.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:

# Update only nominalCapacity for an existing cluster
editCluster(area = "myarea", cluster_name = "mycluster", nominalcapacity = 10600.000)

## End(Not run)
```

editLink

Edit a link between two areas

Description

Edit a link between two areas

Usage

```
editLink(from, to, hurdles_cost = NULL, transmission_capacities = NULL,
display_comments = NULL, filter_synthesis = NULL,
filter_year_by_year = NULL, dataLink = NULL,
opts = antaresRead::simOptions())
```


Arguments

from	The first area from which to create a link
to	The second one
hurdles_cost	Logical, which is used to state whether (linear) transmission fees should be taken into account or not in economy and adequacy simulations
transmission_capacities	Character, one of enabled, ignore or infinite, which is used to state whether the capacities to consider are those indicated in 8760-hour arrays or if zero or infinite values should be used instead (actual values / set to zero / set to infinite)
display_comments	Logical
filter_synthesis	Output synthesis
filter_year_by_year	Output year-by-year
dataLink	a matrix with five column corresponding to : trans. capacity (direct) trans. capacity (indirect), impedances, hurdles cost (direct), hurdles cost (indirect). If NULL (default), a matrix whose rows are equal to 1, 1, 0, 0, 0 is set. See Details
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>

Details

The five times-series are:

- "NTC direct"the upstream-to-downstream capacity, in MW
- "NTC indirect"the downstream-to-upstream capacity, in MW
- "Impedances"virtual impedances that are used in economy simulations to give a physical meaning to raw outputs, when no binding constraints have been defined to enforce Kirchhoff's laws.
- "Hurdle cost direct"an upstream-to-downstream transmission fee, in euro/MWh
- "Hurdle cost indirect"a downstream-to-upstream transmission fee, in euro/MWh

Value

An updated list containing various information about the simulation.

Note

In Antares, areas are sorted in alphabetical order to establish links between. For example, link between "fr" and "be" will appear under "be". So the areas are sorted before creating the link between them, and `dataLink` is rearranged to match the new order.

Examples

```
## Not run:
editLink(
  from = "area1",
  to = "area2",
  transmission_capacities = "infinite"
)

## End(Not run)
```

filteringOptions	<i>Output profile options for creating an area</i>
------------------	--

Description

Output profile options for creating an area

Usage

```
filteringOptions(filter_synthesis = c("hourly", "daily", "weekly",
  "monthly", "annual"), filter_year_by_year = c("hourly", "daily",
  "weekly", "monthly", "annual"))
```

Arguments

```
filter_synthesis
  Output synthesis

filter_year_by_year
  Output Year-by-year
```

Value

a named list

Examples

```
filteringOptions()
```

getPlaylist	<i>Get the playlist of an Antares study</i>
-------------	---

Description

getPlaylist gives the identifier of the MC years which will be simulated in the Antares study, taking into account the potential use of a playlist which can skip some MC years

Usage

```
getPlaylist(opts = antaresRead::simOptions())
```

Arguments

opts list of simulation parameters returned by the function antaresRead::setSimulationPath

Value

Returns a vector of the identifier of the simulated MC year

nodalOptimizationOptions	<i>Nodal optimization parameters for creating an area</i>
--------------------------	---

Description

Nodal optimization parameters for creating an area

Usage

```
nodalOptimizationOptions(non_dispatchable_power = TRUE,  
  dispatchable_hydro_power = TRUE, other_dispatchable_power = TRUE,  
  spread_unsupplied_energy_cost = 0, spread_spilled_energy_cost = 0)
```

Arguments

non_dispatchable_power
 logical, default to FALSE

dispatchable_hydro_power
 logical, default to FALSE

other_dispatchable_power
 logical, default to FALSE

spread_unsupplied_energy_cost
 numeric, default to 0

spread_spilled_energy_cost
 numeric, default to 0

Value

a named list

Examples

```
nodalOptimizationOptions()
```

propertiesLinkOptions *Properties for creating a link*

Description

Properties for creating a link

Usage

```
propertiesLinkOptions(hurdles_cost = FALSE,
  transmission_capacities = "enabled", display_comments = TRUE,
  filter_synthesis = c("hourly", "daily", "weekly", "monthly", "annual"),
  filter_year_by_year = c("hourly", "daily", "weekly", "monthly",
    "annual"))
```

Arguments

hurdles_cost	Logical, which is used to state whether (linear) transmission fees should be taken into account or not in economy and adequacy simulations
transmission_capacities	Character, one of enabled, ignore or infinite, which is used to state whether the capacities to consider are those indicated in 8760-hour arrays or if zero or infinite values should be used instead (actual values / set to zero / set to infinite)
display_comments	Logical
filter_synthesis	Output synthesis
filter_year_by_year	Output year-by-year

Value

A named list

Examples

```
## Not run:
propertiesLinkOptions()

## End(Not run)
```

readIniFile	<i>Read a INI file</i>
-------------	------------------------

Description

Read a INI file

Usage

```
readIniFile(file, stringsAsFactors = FALSE)
```

Arguments

file	file path.
stringsAsFactors	logical: should character vectors be converted to factors?

Value

A list with an element for each section of the .ini file.

removeArea	<i>Remove An Area From inputs</i>
------------	-----------------------------------

Description

Remove An Area From inputs

Usage

```
removeArea(name, opts = antaresRead::simOptions())
```

Arguments

name	An area name
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
removeArea("fictive_area")

## End(Not run)
```

```
removeBindingConstraint
    Remove a Binding Constraint
```

Description

Remove a Binding Constraint

Usage

```
removeBindingConstraint(name, opts = antaresRead::simOptions())
```

Arguments

name	Name(s) of the binding constraint(s) to remove.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
removeBindingConstraint("mybindingconstraint")

## End(Not run)
```

```
removeCluster    Remove a cluster
```

Description

Remove a cluster

Usage

```
removeCluster(area, cluster_name, add_prefix = TRUE,
  opts = antaresRead::simOptions())
```

Arguments

area	Area from which to remove a cluster.
cluster_name	Cluster to remove.
add_prefix	If TRUE, cluster_name will be prefixed by area's name.
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
createCluster(area = "fr", cluster_name = "fr_gas",
              group = "other", `marginal-cost` = 50)

removeCluster(area = "fr", cluster_name = "fr_gas")

## End(Not run)
```

 removeLink

Remove a link between two ares

Description

Remove a link between two ares

Usage

```
removeLink(from, to, opts = antaresRead::simOptions())
```

Arguments

from	The first area from which to create a link
to	The second one
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

An updated list containing various information about the simulation.

Examples

```
## Not run:
createLink(from = "myarea", to = "myarea2")
removeLink(from = "myarea", to = "myarea2")

## End(Not run)
```

runSimulation *Run an Antares Simulation*

Description

run_simulation is a function which runs an ANTARES study in economic mode

Usage

```
runSimulation(name, mode = "economy",
  path_solver = getOption("antares.solver"), wait = TRUE,
  show_output_on_console = FALSE, parallel = TRUE,
  opts = antaresRead::simOptions())
```

Arguments

name	Name of the simulation.
mode	Simulation mode, can take value "economy", "adequacy" or "draft".
path_solver	Character containing the Antares Solver path
wait	Logical, indicating whether the R interpreter should wait for the simulation to finish, or run it asynchronously.
show_output_on_console	Logical, indicating whether to capture the ANTARES log and show it on the R console.
parallel	Logical. If TRUE the ANTARES simulation will be run in parallel mode (Work only with ANTARES v6.0.0 or more). In that case, the number of cores used by the simulation is the one set in advanced_settings/simulation_cores (see ANTARES interface).
opts	List of simulation parameters returned by the function antaresRead::setSimulationPath

Value

The function does not return anything. It is used to launch an ANTARES simulation

runTsGenerator *Run Time-Series Generator*

Description

Run Time-Series Generator

Usage

```
runTsGenerator(path_solver = getOption("antares.solver"), wait = TRUE,
  show_output_on_console = FALSE, opts = antaresRead::simOptions())
```


Arguments

path_solver	Character containing the Antares Solver path.
wait	Logical, indicating whether the R interpreter should wait for the simulation to finish, or run it asynchronously.
show_output_on_console	Logical, indicating whether to capture the ANTARES log and show it on the R console.
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code> .

Examples

```
## Not run:
library(antaresRead)
setSimulationPath(path = "path/to/study")
library(antaresEditObject)
runTsGenerator(
  path_solver = "path/to/antares-6.0-solver.exe",
  show_output_on_console = TRUE
)

## End(Not run)
```

scenario-builder *Read, create & update scenario builder*

Description

Read, create & update scenario builder

Usage

```
scenarioBuilder(n_scenario, n_mc = NULL, areas = NULL,
  areas_rand = NULL, opts = antaresRead::simOptions())

readScenarioBuilder(ruleset = "Default Ruleset", as_matrix = TRUE,
  opts = antaresRead::simOptions())

updateScenarioBuilder(ldata, ruleset = "Default Ruleset",
  series = NULL, opts = antaresRead::simOptions())
```

Arguments

n_scenario	Number of scenario.
n_mc	Number of Monte-Carlo years.
areas	Areas to use in scenario builder, if NULL (default), areas in Antares study are used.

areas_rand	Areas for which to use "rand".
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>
ruleset	Ruleset to read.
as_matrix	If TRUE (default) return a matrix, else a list.
ldata	A matrix obtained with <code>scenarioBuilder</code> , or a named list of matrix obtained with <code>scenarioBuilder</code> , names must be 'l', 'h', 'w' or 's', depending the serie to update.
series	Name(s) of the serie(s) to update if <code>ldata</code> is a single matrix.

Value

`scenarioBuilder` : a matrix
`readScenarioBuilder` : a list of matrix or list

Examples

```
## Not run:

library(antaresRead)
library(antaresEditObject)

# simulation path
setSimulationPath(
  path = "pat/to/simulation",
  simulation = "input"
)

# Create a scenario builder matrix
sbuilder <- scenarioBuilder(
  n_scenario = 51,
  n_mc = 2040,
  areas_rand = c("fr", "be")
)
sbuilder[, 1:6]
dim(sbuilder)

# Read previous scenario builder
# in a matrix format
prev_sb <- readScenarioBuilder()

# Update scenario builder

# for load serie
updateScenarioBuilder(ldata = sbuilder, series = "load")

# equivalent as
updateScenarioBuilder(ldata = list(l = sbuilder))
```

```
# update several series

# same input
sbuilder
updateScenarioBuilder(
  ldata = sbuilder,
  series = c("load", "hydro", "solar")
)

# different input
updateScenarioBuilder(ldata = list(
  l = load_sb,
  h = hydro_sb,
  s = solar_sb
))

## End(Not run)
```

setPlaylist

Set the playlist of an Antares Study

Description

set_playlist is a function which modifies the input file of an ANTARES study and set the playlist in order to simulate only the MC years given in input

Usage

```
setPlaylist(playlist, opts = antaresRead::simOptions())
```

Arguments

playlist	vector of MC years identifier to be simulated
opts	list of simulation parameters returned by the function antaresRead::setSimulationPath

Value

The function does not return anything. It is used to modify the input of an Antares study

setSolverPath	<i>Set path to Antares Solver</i>
---------------	-----------------------------------

Description

Set path to Antares Solver

Usage

```
setSolverPath(path)
```

Arguments

path	(optional) Path to the solver (e.g. antares-6.0-solver.exe in \bin directory where Antares is installed). If missing, a window opens and lets the user choose the directory of the simulation interactively.
------	--

Examples

```
## Not run:

setSolverPath(path = "C:/antares/bin/antares-6.0-solver.exe")

## End(Not run)
```

updateGeneralSettings	<i>Update general parameters of an Antares study</i>
-----------------------	--

Description

Update general parameters of an Antares study

Usage

```
updateGeneralSettings(mode = NULL, horizon = NULL, nyears = NULL,
  simulation.start = NULL, simulation.end = NULL, january.1st = NULL,
  first.month.in.year = NULL, first.weekday = NULL, leapyear = NULL,
  year.by.year = NULL, derated = NULL, custom.ts.numbers = NULL,
  user.playlist = NULL, filtering = NULL,
  active.rules.scenario = NULL, generate = NULL,
  nbtimeseriesload = NULL, nbtimeserieshydro = NULL,
  nbtimeserieswind = NULL, nbtimeseriesthermal = NULL,
  nbtimeseriessolar = NULL, refreshtimeseries = NULL,
```

```

intra.modal = NULL, inter.modal = NULL, refreshintervalload = NULL,
refreshintervalhydro = NULL, refreshintervalwind = NULL,
refreshintervalthermal = NULL, refreshinterval solar = NULL,
readonly = NULL, opts = antaresRead::simOptions()

```

Arguments

mode	Economy, Adequacy, Draft.
horizon	Reference year (static tag, not used in the calculations)
nbyears	Number of Monte-Carlo years that should be prepared for the simulation (not always the same as the Number of MC years actually simulated, see 'selection mode' below).
simulation.start	First day of the simulation (e.g. 8 for a simulation beginning on the second week of the first month of the year)
simulation.end	Last day of the simulation (e.g. 28 for a simulation ending on the fourth week of the first month of the year)
january.1st	First day of the year (Mon, Tue, etc.).
first.month.in.year	Actual month by which the Time-series begin (Jan to Dec, Oct to Sep, etc.)
first.weekday	In economy or adequacy simulations, indicates the frame (Mon- Sun, Sat-Fri, etc.) to use for the edition of weekly results.
leapyear	(TRUE/FALSE) indicates whether February has 28 or 29 days.
year.by.year	(False) No individual results will be printed out, (True) For each simulated year, detailed results will be printed out in an individual directory7 : Study_name/OUTPUT/simu_tag/Economy/mc-i-number
derated	See Antares General Reference Guide.
custom.ts.numbers	See Antares General Reference Guide.
user.playlist	See Antares General Reference Guide.
filtering	See Antares General Reference Guide.
active.rules.scenario	See Antares General Reference Guide.
generate	See Antares General Reference Guide.
nbtimeseriesload	See Antares General Reference Guide.
nbtimeserieshydro	See Antares General Reference Guide.
nbtimeserieswind	See Antares General Reference Guide.
nbtimeseriesthermal	See Antares General Reference Guide.
nbtimeseriessolar	See Antares General Reference Guide.

refreshtimeseries	See Antares General Reference Guide.
intra.modal	See Antares General Reference Guide.
inter.modal	See Antares General Reference Guide.
refreshintervalload	See Antares General Reference Guide.
refreshintervalhydro	See Antares General Reference Guide.
refreshintervalwind	See Antares General Reference Guide.
refreshintervalthermal	See Antares General Reference Guide.
refreshinterval solar	See Antares General Reference Guide.
readonly	See Antares General Reference Guide.
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>

Value

An updated list containing various information about the simulation.

updateOptimizationSettings

Update optimization parameters of an Antares study

Description

Update optimization parameters of an Antares study

Usage

```
updateOptimizationSettings(simplex.range = NULL,
  transmission.capacities = NULL, include.constraints = NULL,
  include.hurdlecosts = NULL, include.tc.min.stable.power = NULL,
  include.tc.min.up.down.time = NULL, include.dayahead = NULL,
  include.strategicreserve = NULL, include.spinningreserve = NULL,
  include.primaryreserve = NULL, include.exportmps = NULL,
  power.fluctuations = NULL, shedding.strategy = NULL,
  shedding.policy = NULL, unit.commitment.mode = NULL,
  number.of.cores.mode = NULL, day.ahead.reserve.management = NULL,
  opts = antaresRead::simOptions())
```

Arguments

simplex.range	week or day
transmission.capacities	true, false or infinite
include.constraints	true or false
include.hurdlecosts	true or false
include.tc.min.stable.power	true or false
include.tc.min.up.down.time	true or false
include.dayahead	true or false
include.strategicreserve	true or false
include.spinningreserve	true or false
include.primaryreserve	true or false
include.exportmps	true or false
power.fluctuations	free modulations, minimize excursions or minimize ramping
shedding.strategy	share margins
shedding.policy	shave peaks or minimize duration
unit.commitment.mode	fast or accurate
number.of.cores.mode	minimum, low, medium, high or maximum
day.ahead.reserve.management	global
opts	List of simulation parameters returned by the function <code>antaresRead::setSimulationPath</code>

Value

An updated list containing various information about the simulation options.

writeIni	<i>Write ini file from list obtain by antaresRead:::readIniFile and modify by user</i>
----------	--

Description

Write ini file from list obtain by antaresRead:::readIniFile and modify by user

Usage

```
writeIni(listData, pathIni, overwrite = FALSE)
```

Arguments

listData	list, modified list obtained by antaresRead:::readIniFile.
pathIni	Character, Path to ini file.
overwrite	logical, should file be overwritten if already exist?

Examples

```
## Not run:  
pathIni <- "D:/exemple_test/settings/generaldata.ini"  
generalSetting <- antaresRead:::readIniFile(pathIni)  
generalSetting$output$synthesis <- FALSE  
writeIni(generalSetting, pathIni)  
  
## End(Not run)
```


Index

backupStudy, 2

checkRemovedArea, 3
createArea, 4
createBindingConstraint, 5
createCluster, 6
createDistrict, 8
createDSR, 9
createLink, 10
createPSP, 12
createStudy, 13

dicoGeneralSettings, 14
dicoOptimizationSettings, 15

editCluster, 15
editDSR (createDSR), 9
editLink, 16
editPSP (createPSP), 12

filteringOptions, 18

getCapacityDSR (createDSR), 9
getCapacityPSP (createPSP), 12
getPlaylist, 19

nodalOptimizationOptions, 19

propertiesLinkOptions, 20

readIniFile, 21
readScenarioBuilder (scenario-builder),
25

removeArea, 21
removeBindingConstraint, 22
removeCluster, 22
removeLink, 23
runSimulation, 24
runTsGenerator, 24

scenario-builder, 25

scenarioBuilder (scenario-builder), 25
setPlaylist, 27
setSolverPath, 28

updateGeneralSettings, 28
updateOptimizationSettings, 30
updateScenarioBuilder
(scenario-builder), 25

writeIni, 32