

# Package ‘bigrquery’

August 5, 2021

**Title** An Interface to Google's 'BigQuery' 'API'

**Version** 1.4.0

**Description** Easily talk to Google's 'BigQuery' database from R.

**License** GPL-3

**URL** <https://bigrquery.r-dbi.org>, <https://github.com/r-dbi/bigrquery>

**BugReports** <https://github.com/r-dbi/bigrquery/issues>

**Depends** R (>= 3.3)

**Imports** assertthat, bit64, curl, DBI, gargle (>= 1.2.0), glue (>= 1.3.0), httr, lifecycle, jsonlite, methods, prettyunits, progress, Rcpp, rlang (>= 0.4.9), tibble

**Suggests** blob, covr, DBItest, dbplyr (>= 1.3.0), dplyr (>= 0.7.0), hms, readr, sodium, testthat (>= 2.1.0), withr, wk (>= 0.3.2)

**LinkingTo** progress, rapidjsonr, Rcpp

**Encoding** UTF-8

**RoxygenNote** 7.1.1.9001

**Collate** 'RcppExports.R' 'bigrquery.R' 'bq-auth.R' 'bq-dataset.R' 'bq-download.R' 'bq-field.R' 'bq-job.R' 'bq-param.R' 'bq-parse.R' 'bq-perform.R' 'bq-project.R' 'bq-projects.R' 'bq-query.R' 'bq-refs.R' 'bq-request.R' 'bq-table.R' 'bq-test.R' 'camelCase.R' 'dbi-driver.R' 'dbi-connection.R' 'dbi-result.R' 'dplyr.R' 'gs-object.R' 'old-auth.R' 'old-dataset.R' 'old-id.R' 'old-job-extract.R' 'old-job-query.R' 'old-job-upload.R' 'old-job.R' 'old-project.R' 'old-projects.R' 'old-query.R' 'old-table.R' 'old-tabledata.R' 'utils.R' 'zzz.R'

**NeedsCompilation** yes

**Author** Hadley Wickham [aut, cre] (<<https://orcid.org/0000-0003-4757-117X>>), Jennifer Bryan [aut] (<<https://orcid.org/0000-0002-6983-2759>>), Kungliga Tekniska Högskolan [ctb] (strptime implementation), The NetBSD Foundation, Inc. [ctb] (gmtime implementation), RStudio [cph, fnd]

**Maintainer** Hadley Wickham <hadley@rstudio.com>

**Repository** CRAN

**Date/Publication** 2021-08-05 04:20:35 UTC

## R topics documented:

api-dataset . . . . .	2
api-job . . . . .	4
api-project . . . . .	5
api-table . . . . .	6
bigquery . . . . .	8
bq_auth . . . . .	9
bq_auth_configure . . . . .	11
bq_deauth . . . . .	13
bq_field . . . . .	13
bq_has_token . . . . .	14
bq_projects . . . . .	15
bq_query . . . . .	15
bq_refs . . . . .	17
bq_table_download . . . . .	18
bq_token . . . . .	20
bq_user . . . . .	21
src_bigquery . . . . .	21
<b>Index</b>	<b>23</b>

---

api-dataset	<i>BigQuery datasets</i>
-------------	--------------------------

---

### Description

Basic create-read-update-delete verbs for datasets.

### Usage

```
bq_dataset_create(x, location = "US", ...)
```

```
bq_dataset_meta(x, fields = NULL)
```

```
bq_dataset_exists(x)
```

```
bq_dataset_update(x, ...)
```

```
bq_dataset_delete(x, delete_contents = FALSE)
```

```
bq_dataset_tables(x, page_size = 50, max_pages = Inf, warn = TRUE, ...)
```

## Arguments

x	A <a href="#">bq_dataset</a>
location	Dataset location
...	Additional arguments passed on to the underlying API call. snake_case names are automatically converted to camelCase.
fields	An optional field specification for <a href="#">partial response</a>
delete_contents	If TRUE, will recursively delete all tables in the dataset. Set to FALSE by default for safety.
page_size	Number of items per page.
max_pages	Maximum number of pages to retrieve. Use Inf to retrieve all pages (this may take a long time!)
warn	If TRUE, warn when there are unretrieved pages.

## Google BigQuery API documentation

- [get](#)
- [insert](#)
- [delete](#)
- [list](#)

## Examples

```
if (bq_testable()) {
  ds <- bq_dataset(bq_test_project(), "dataset_api")
  bq_dataset_exists(ds)

  bq_dataset_create(ds)
  bq_dataset_exists(ds)
  str(bq_dataset_meta(ds))

  bq_dataset_delete(ds)
  bq_dataset_exists(ds)

  # Use bq_test_dataset() to create a temporary dataset that will
  # be automatically deleted
  ds <- bq_test_dataset()
  bq_table_create(bq_table(ds, "x1"))
  bq_table_create(bq_table(ds, "x2"))
  bq_table_create(bq_table(ds, "x3"))
  bq_dataset_tables(ds)
}
```

---

`api-job`*BigQuery job: retrieve metadata*

---

## Description

To perform a job, see [api-perform](#). These functions all retrieve metadata (in various forms) about an existing job.

## Usage

```
bq_job_meta(x, fields = NULL)
```

```
bq_job_status(x)
```

```
bq_job_show_statistics(x)
```

```
bq_job_wait(x, quiet = getOption("bigrquery.quiet"), pause = 0.5)
```

## Arguments

<code>x</code>	A <a href="#">bq_job</a>
<code>fields</code>	An optional field specification for <a href="#">partial response</a>
<code>quiet</code>	If FALSE, displays progress bar; if TRUE is silent; if NA displays progress bar only for long-running jobs.
<code>pause</code>	amount of time to wait between status requests

## Google BigQuery API documentation

- [get](#)

## Examples

```
if (bq_testable()) {  
  jobs <- bq_project_jobs(bq_test_project())  
  jobs[[1]]  
  
  # Show statistics about job  
  bq_job_show_statistics(jobs[[1]])  
  
  # Wait for job to complete  
  bq_job_wait(jobs[[1]])  
}
```

---

`api-project`*BigQuery project methods*

---

### Description

Projects have two primary components: datasets and jobs. Unlike other BigQuery objects, is no accompanying `bq_project` S3 class because a project is a simple string.

### Usage

```
bq_project_datasets(x, page_size = 100, max_pages = 1, warn = TRUE)
```

```
bq_project_jobs(x, page_size = 100, max_pages = 1, warn = TRUE)
```

### Arguments

<code>x</code>	A string giving a project name.
<code>page_size</code>	Number of items per page.
<code>max_pages</code>	Maximum number of pages to retrieve. Use <code>Inf</code> to retrieve all pages (this may take a long time!)
<code>warn</code>	If <code>TRUE</code> , warn when there are unretrieved pages.

### Value

- `bq_project_datasets()`: a list of [bq\\_datasets](#)
- `bq_project_jobs()`: a list of [bq\\_jobs](#).

### Google BigQuery API documentation

- [datasets](#)
- [jobs](#)

One day we might also expose the general [project metadata](#).

### Examples

```
if (bq_authable()) {  
  bq_project_datasets("bigquery-public-data")  
  bq_project_datasets("githubarchive")  
}  
  
if (bq_testable()) {  
  bq_project_jobs(bq_test_project(), page_size = 10)  
}
```

api-table

*BigQuery tables***Description**

Basic create-read-update-delete verbs for tables, as well as functions for uploading and downloading data in to/from memory (`bq_table_upload()`, `bq_table_download()`), and saving to/loading from Google Cloud Storage (`bq_table_load()`, `bq_table_save()`).

**Usage**

```

bq_table_create(x, fields = NULL, ...)

bq_table_meta(x, fields = NULL)

bq_table_fields(x)

bq_table_size(x)

bq_table_nrow(x)

bq_table_exists(x)

bq_table_delete(x)

bq_table_copy(x, dest, ..., quiet = NA)

bq_table_upload(x, values, ..., quiet = NA)

bq_table_save(x, destination_uris, ..., quiet = NA)

bq_table_load(x, source_uris, ..., quiet = NA)

bq_table_patch(x, fields)

```

**Arguments**

<code>x</code>	A <a href="#">bq_table</a> , or an object coercible to a <code>bq_table</code> .
<code>fields</code>	A <a href="#">bq_fields</a> specification, or something coercible to it (like a data frame).
<code>...</code>	Additional arguments passed on to the underlying API call. <code>snake_case</code> names are automatically converted to camelCase.
<code>dest</code>	Source and destination <a href="#">bq_tables</a> .
<code>quiet</code>	If <code>FALSE</code> , displays progress bar; if <code>TRUE</code> is silent; if <code>NA</code> displays progress bar only for long-running jobs.
<code>values</code>	Data frame of values to insert.

destination_uris	A character vector of fully-qualified Google Cloud Storage URIs where the extracted table should be written. Can export up to 1 Gb of data per file. Use a wild card URI (e.g. gs://[YOUR_BUCKET]/file-name-*.json) to automatically create any number of files.
source_uris	The fully-qualified URIs that point to your data in Google Cloud. For Google Cloud Storage URIs: Each URI can contain one "*" wildcard character and it must come after the 'bucket' name. Size limits related to load jobs apply to external data sources. For Google Cloud Bigtable URIs: Exactly one URI can be specified and it has to be a fully specified and valid HTTPS URL for a Google Cloud Bigtable table. For Google Cloud Datastore backups: Exactly one URI can be specified. Also, the "*" wildcard character is not allowed.

### Value

- `bq_table_copy()`, `bq_table_create()`, `bq_table_delete()`, `bq_table_upload()`: an invisible [bq\\_table](#)
- `bq_table_exists()`: either TRUE or FALSE.
- `bq_table_download()`: a data frame
- `bq_table_size()`: the size of the table in bytes
- `bq_table_fields()`: a [bq\\_fields](#).

### Google BigQuery API documentation

- [insert](#)
- [get](#)
- [delete](#)

### Examples

```
if (bq_testable()) {
  ds <- bq_test_dataset()

  bq_mtcars <- bq_table_create(
    ds,
    "mtcars",
    friendly_name = "Motor Trend Car Road Tests",
    description = "The data was extracted from the 1974 Motor Trend US magazine",
    labels = list(category = "example")
  )
  bq_mtcars <- bq_table(ds, "mtcars")
  bq_table_exists(bq_mtcars)

  bq_table_upload(bq_mtcars, mtcars)
  bq_table_exists(bq_mtcars)

  bq_table_fields(bq_mtcars)
```

```

bq_table_size(bq_mtcars)
str(bq_table_meta(bq_mtcars))

bq_table_delete(bq_mtcars)
bq_table_exists(bq_mtcars)

my_natality <- bq_table(ds, "mynatality")
bq_table_copy("publicdata.samples.natality", my_natality)
}

```

bigquery

*BigQuery DBI driver***Description**

Creates a BigQuery DBI driver for use in `DBI::dbConnect()`.

**Usage**

```

## S4 method for signature 'BigQueryDriver'
dbConnect(
  drv,
  project,
  dataset = NULL,
  billing = project,
  page_size = 10000,
  quiet = NA,
  use_legacy_sql = FALSE,
  bigint = c("integer", "integer64", "numeric", "character"),
  ...
)

```

**Arguments**

<code>drv</code>	an object that inherits from <code>DBIDriver</code> , or an existing <code>DBIConnection</code> object (in order to clone an existing connection).
<code>project, dataset</code>	Project and dataset identifiers
<code>billing</code>	Identifier of project to bill.
<code>page_size</code>	Number of items per page.
<code>quiet</code>	If <code>FALSE</code> , displays progress bar; if <code>TRUE</code> is silent; if <code>NA</code> displays progress bar only for long-running jobs.
<code>use_legacy_sql</code>	If <code>TRUE</code> will use BigQuery's legacy SQL format.
<code>bigint</code>	The R type that BigQuery's 64-bit integer types should be mapped to. The default is <code>"integer"</code> which returns R's <code>integer</code> type but results in <code>NA</code> for values above/below $\pm 2147483647$ . <code>"integer64"</code> returns a <code>bit64::integer64</code> , which allows the full range of 64 bit integers.
<code>...</code>	Other arguments for compatibility with generic; currently ignored.



**Examples**

```

if (bq_testable()) {
  con <- DBI::dbConnect(
    bigquery(),
    project = "publicdata",
    dataset = "samples",
    billing = bq_test_project()
  )
  con
  DBI::dbListTables(con)
  DBI::dbReadTable(con, "natality", n_max = 10)

  # Create a temporary dataset to explore
  ds <- bq_test_dataset()
  con <- DBI::dbConnect(
    bigquery(),
    project = ds$project,
    dataset = ds$dataset
  )
  DBI::dbWriteTable(con, "mtcars", mtcars)
  DBI::dbReadTable(con, "mtcars")[1:6, ]

  DBI::dbGetQuery(con, "SELECT count(*) FROM mtcars")

  res <- DBI::dbSendQuery(con, "SELECT cyl, mpg FROM mtcars")
  dbColumnInfo(res)
  dbFetch(res, 10)
  dbFetch(res, -1)
  DBI::dbHasCompleted(res)
}

```

---

**bq\_auth***Authorize bigrquery*

---

**Description**

Authorize bigrquery to view and manage your BigQuery projects. This function is a wrapper around [gargle::token\\_fetch\(\)](#).

By default, you are directed to a web browser, asked to sign in to your Google account, and to grant bigrquery permission to operate on your behalf with Google BigQuery. By default, with your permission, these user credentials are cached in a folder below your home directory, from where they can be automatically refreshed, as necessary. Storage at the user level means the same token can be used across multiple projects and tokens are less likely to be synced to the cloud by accident.

If you are interacting with R within a browser (applies to RStudio Server, RStudio Workbench, and RStudio Cloud), you need a variant of this flow, known as out-of-band auth ("oob"). If this does not happen automatically, you can request it yourself with `use_oob = TRUE` or, more persistently, by setting an option via `options(gargle_oob_default = TRUE)`.

**Usage**

```

bq_auth(
  email = gargle::gargle_oauth_email(),
  path = NULL,
  scopes = c("https://www.googleapis.com/auth/bigquery",
             "https://www.googleapis.com/auth/cloud-platform"),
  cache = gargle::gargle_oauth_cache(),
  use_oob = gargle::gargle_oob_default(),
  token = NULL
)

```

**Arguments**

email	Optional. Allows user to target a specific Google identity. If specified, this is used for token lookup, i.e. to determine if a suitable token is already available in the cache. If no such token is found, email is used to pre-select the targetted Google identity in the OAuth chooser. Note, however, that the email associated with a token when it's cached is always determined from the token itself, never from this argument. Use NA or FALSE to match nothing and force the OAuth dance in the browser. Use TRUE to allow email auto-discovery, if exactly one matching token is found in the cache. Specify just the domain with a glob pattern, e.g. <code>"*@example.com"</code> , to create code that "just works" for both <code>alice@example.com</code> and <code>bob@example.com</code> . Defaults to the option named <code>"gargle_oauth_email"</code> , retrieved by <code>gargle_oauth_email()</code> .
path	JSON identifying the service account, in one of the forms supported for the <code>txt</code> argument of <code>jsonlite::fromJSON()</code> (typically, a file path or JSON string).
scopes	A character vector of scopes to request. Pick from those listed at <a href="https://developers.google.com/identity/protocols/oauth2/scopes">https://developers.google.com/identity/protocols/oauth2/scopes</a> .
cache	Specifies the OAuth token cache. Defaults to the option named <code>"gargle_oauth_cache"</code> , retrieved via <code>gargle_oauth_cache()</code> .
use_oob	Whether to prefer "out of band" authentication. Defaults to the option named <code>"gargle_oob_default"</code> , retrieved via <code>gargle_oob_default()</code> .
token	A token with class <code>Token2.0</code> or an object of <code>httr</code> 's class <code>request</code> , i.e. a token that has been prepared with <code>httr::config()</code> and has a <code>Token2.0</code> in the <code>auth_token</code> component.

**Details**

Most users, most of the time, do not need to call `bq_auth()` explicitly – it is triggered by the first action that requires authorization. Even when called, the default arguments often suffice. However, when necessary, this function allows the user to explicitly:

- Declare which Google identity to use, via an email address. If there are multiple cached tokens, this can clarify which one to use. It can also force bigquery to switch from one identity to another. If there's no cached token for the email, this triggers a return to the browser to choose the identity and give consent. You can specify just the domain by using a glob pattern. This means that a script containing `email = "*@example.com"` can be run without further tweaks on the machine of either `alice@example.com` or `bob@example.com`.

- Use a service account token or workload identity federation.
- Bring their own [Token2.0](#).
- Specify non-default behavior re: token caching and out-of-bound authentication.
- Customize scopes.

For details on the many ways to find a token, see [gargle::token\\_fetch\(\)](#). For deeper control over auth, use [bq\\_auth\\_configure\(\)](#) to bring your own OAuth app or API key. Read more about gargle options, see [gargle::gargle\\_options](#).

### See Also

Other auth functions: [bq\\_auth\\_configure\(\)](#), [bq\\_deauth\(\)](#)

### Examples

```
## Not run:
## load/refresh existing credentials, if available
## otherwise, go to browser for authentication and authorization
bq_auth()

## force use of a token associated with a specific email
bq_auth(email = "jenny@example.com")

## force a menu where you can choose from existing tokens or
## choose to get a new one
bq_auth(email = NA)

## use a 'read only' scope, so it's impossible to change data
bq_auth(
  scopes = "https://www.googleapis.com/auth/devstorage.read_only"
)

## use a service account token
bq_auth(path = "foofy-83ee9e7c9c48.json")

## End(Not run)
```

---

bq\_auth\_configure      *Edit and view auth configuration*

---

### Description

These functions give more control over and visibility into the auth configuration than [bq\\_auth\(\)](#) does. [bq\\_auth\\_configure\(\)](#) lets the user specify their own:

- OAuth app, which is used when obtaining a user token. See the vignette [How to get your own API credentials](#) for more. If the user does not configure these settings, internal defaults are used. [bq\\_oauth\\_app\(\)](#) retrieves the currently configured OAuth app.

**Usage**

```
bq_auth_configure(app, path)
```

```
bq_oauth_app()
```

**Arguments**

app	OAuth app, in the sense of <a href="#">httr::oauth_app()</a> .
path	JSON downloaded from Google Cloud Platform Console, containing a client id (aka key) and secret, in one of the forms supported for the <code>txt</code> argument of <a href="#">jsonlite::fromJSON()</a> (typically, a file path or JSON string).

**Value**

- `bq_auth_configure()`: An object of R6 class [gargle::AuthState](#), invisibly.
- `bq_oauth_app()`: the current user-configured [httr::oauth\\_app\(\)](#).

**See Also**

Other auth functions: [bq\\_auth\(\)](#), [bq\\_deauth\(\)](#)

**Examples**

```
# see the current user-configured OAuth app (probably `NULL`)
bq_oauth_app()

if (require(httr)) {

  # store current state, so we can restore
  original_app <- bq_oauth_app()

  # bring your own app via client id (aka key) and secret
  google_app <- httr::oauth_app(
    "my-awesome-google-api-wrapping-package",
    key = "123456789.apps.googleusercontent.com",
    secret = "abcdefghijklmnopqrstuvwxy"
  )
  bq_auth_configure(app = google_app)

  # confirm current app
  bq_oauth_app()

  # restore original state
  bq_auth_configure(app = original_app)
  bq_oauth_app()
}

## Not run:
# bring your own app via JSON downloaded from GCP Console
bq_auth_configure(
  path = "/path/to/the/JSON/you/downloaded/from/gcp/console.json"
```

```
)
## End(Not run)
```

---

bq_deauth	<i>Clear current token</i>
-----------	----------------------------

---

### Description

Clears any currently stored token. The next time bigquery needs a token, the token acquisition process starts over, with a fresh call to `bq_auth()` and, therefore, internally, a call to `gargle::token_fetch()`. Unlike some other packages that use gargle, bigquery is not usable in a de-authorized state. Therefore, calling `bq_deauth()` only clears the token, i.e. it does NOT imply that subsequent requests are made with an API key in lieu of a token.

### Usage

```
bq_deauth()
```

### See Also

Other auth functions: `bq_auth_configure()`, `bq_auth()`

### Examples

```
## Not run:
bq_deauth()

## End(Not run)
```

---

bq_field	<i>BigQuery field (and fields) class</i>
----------	--

---

### Description

`bq_field()` and `bq_fields()` create; `as_bq_field()` and `as_bq_fields()` coerce from lists.

### Usage

```
bq_field(name, type, mode = "NULLABLE", fields = list(), description = NULL)

bq_fields(x)

as_bq_field(x)

as_bq_fields(x)
```

**Arguments**

name	Field name
type	Field type
mode	Field mode
fields	For a field of type "record", a list of sub-fields.
description	Field description
x	A list of bq_fields

**Examples**

```
bq_field("name", "string")

as_bq_fields(list(
  list(name = "name", type = "string"),
  bq_field("age", "integer")
))

# as_bq_fields() can also take a data frame
as_bq_fields(mtcars)
```

---

bq_has_token	<i>Is there a token on hand?</i>
--------------	----------------------------------

---

**Description**

Reports whether bigquery has stored a token, ready for use in downstream requests.

**Usage**

```
bq_has_token()
```

**Value**

Logical.

**See Also**

Other low-level API functions: [bq\\_token\(\)](#)

**Examples**

```
bq_has_token()
```

---

bq_projects	<i>List available projects</i>
-------------	--------------------------------

---

### Description

List all projects that you have access to. You can also work with [public datasets](#), but you will need to provide a billing project whenever you perform any non-free operation.

### Usage

```
bq_projects(page_size = 100, max_pages = 1, warn = TRUE)
```

### Arguments

page_size	Number of items per page.
max_pages	Maximum number of pages to retrieve. Use Inf to retrieve all pages (this may take a long time!)
warn	If TRUE, warn when there are unretrieved pages.

### Value

A character vector.

### Google BigQuery API documentation

- [list](#)

### Examples

```
if (bq_authable()) {  
  bq_projects()  
}
```

---

bq_query	<i>Submit query to BigQuery</i>
----------	---------------------------------

---

### Description

These submit a query (using [bq\\_perform\\_query\(\)](#)) and then wait for it complete (with [bq\\_job\\_wait\(\)](#)). All BigQuery queries save their results into a table (temporary or otherwise), so these functions return a [bq\\_table](#) which you can then query for more information.

**Usage**

```
bq_project_query(x, query, destination_table = NULL, ..., quiet = NA)
```

```
bq_dataset_query(
  x,
  query,
  destination_table = NULL,
  ...,
  billing = NULL,
  quiet = NA
)
```

**Arguments**

x	Either a project (a string) or a <a href="#">bq_dataset</a> .
query	SQL query string.
destination_table	A <a href="#">bq_table</a> where results should be stored. If not supplied, results will be saved to a temporary table that lives in a special dataset. You must supply this parameter for large queries (> 128 MB compressed).
...	Passed on to <a href="#">bq_perform_query()</a>
quiet	If FALSE, displays progress bar; if TRUE is silent; if NA displays progress bar only for long-running jobs.
billing	If you query a dataset that you only have read access for, such as a public dataset, you must also submit a billing project.

**Value**

A [bq\\_table](#)

**Examples**

```
if (bq_testable()) {
# Querying a project requires full name in query
tb <- bq_project_query(
  bq_test_project(),
  "SELECT count(*) FROM publicdata.samples.nativity"
)
bq_table_fields(tb)
bq_table_download(tb)

# Querying a dataset sets default dataset so you can use bare table name,
# but for public data, you'll need to set a project to bill.
ds <- bq_dataset("publicdata", "samples")
tb <- bq_dataset_query(ds,
  query = "SELECT count(*) FROM nativity",
  billing = bq_test_project()
)
bq_table_download(tb)
```



```

tb <- bq_dataset_query(ds,
  query = "SELECT count(*) FROM natality WHERE state = @state",
  parameters = list(state = "KS"),
  billing = bq_test_project()
)
bq_table_download(tb)
}

```

---

bq\_refs

*S3 classes that reference remote BigQuery datasets, tables and jobs*


---

## Description

Create references to BigQuery datasets, jobs, and tables. Each class has a constructor function (`bq_dataset()`, `bq_table()`, `bq_job()`) and a coercion function (`as_bq_dataset()`, `as_bq_table()`, `as_bq_job()`). The coercion functions come with methods for strings (which find components by splitting on `.`), and lists (which look for named components like `projectId` or `project_id`).

All `bq_table_`, `bq_dataset_` and `bq_job_` functions call the appropriate coercion functions on their first argument, allowing you to flexibly specify their inputs.

## Usage

```

bq_dataset(project, dataset)

as_bq_dataset(x)

bq_table(project, dataset, table = NULL)

as_bq_table(x, ...)

bq_job(project, job, location = "US")

as_bq_job(x)

```

## Arguments

project, dataset, table, job	Individual project, dataset, table, and job identifiers (strings). For <code>bq_table()</code> , you if supply a <code>bq_dataset</code> as the first argument, the 2nd argument will be interpreted as the table
x	An object to coerce to a <code>bq_job</code> , <code>bq_dataset</code> , or <code>bq_table</code> . Built-in methods handle strings and lists.
...	Other arguments passed on to methods.
location	Job location

**See Also**

[api-job](#), [api-perform](#), [api-dataset](#), and [api-table](#) for functions that work with these objects.

**Examples**

```
# Creation -----
samples <- bq_dataset("publicdata", "samples")
natality <- bq_table("publicdata", "samples", "natality")
natality

# Or
bq_table(samples, "natality")

bq_job("bigquery-examples", "m0SgFu2ycbbge6jgcvzvf1BJ_Wft")

# Coercion -----
as_bq_dataset("publicdata.shakespeare")
as_bq_table("publicdata.samples.natality")

as_bq_table(list(
  project_id = "publicdata",
  dataset_id = "samples",
  table_id = "natality"
))

as_bq_job(list(
  projectId = "bigquery-examples",
  jobId = "job_m0SgFu2ycbbge6jgcvzvf1BJ_Wft",
  location = "US"
))
```

---

bq\_table\_download      *Download table data*

---

**Description**

This retrieves rows in chunks of `page_size`. It is most suitable for results of smaller queries (<100 MB, say). For larger queries, it is better to export the results to a CSV file stored on google cloud and use the bq command line tool to download locally.

**Usage**

```
bq_table_download(
  x,
  n_max = Inf,
  page_size = NULL,
  start_index = 0L,
  max_connections = 6L,
```

```

  quiet = NA,
  bigint = c("integer", "integer64", "numeric", "character"),
  max_results = deprecated()
)

```

### Arguments

x	A <a href="#">bq_table</a>
n_max	Maximum number of results to retrieve. Use Inf to retrieve all rows.
page_size	The number of rows requested per chunk. It is recommended to leave this unspecified until you have evidence that the page_size selected automatically by <code>bq_table_download()</code> is problematic. When <code>page_size = NULL</code> bigquery determines a conservative, natural chunk size empirically. If you specify the <code>page_size</code> , it is important that each chunk fits on one page, i.e. that the requested row limit is low enough to prevent the API from paginating based on response size.
start_index	Starting row index (zero-based).
max_connections	Number of maximum simultaneous connections to BigQuery servers.
quiet	If FALSE, displays progress bar; if TRUE is silent; if NA displays progress bar only for long-running jobs.
bigint	The R type that BigQuery's 64-bit integer types should be mapped to. The default is "integer", which returns R's integer type, but results in NA for values above/below +/- 2147483647. "integer64" returns a <code>bit64::integer64</code> , which allows the full range of 64 bit integers.
max_results	<b>[Deprecated]</b> Deprecated. Please use <code>n_max</code> instead.

### Value

Because data retrieval may generate list-columns and the `data.frame` print method can have problems with list-columns, this method returns a tibble. If you need a `data.frame`, coerce the results with `as.data.frame()`.

### Complex data

bigquery will retrieve nested and repeated columns in to list-columns as follows:

- Repeated values (arrays) will become a list-column of vectors.
- Records will become list-columns of named lists.
- Repeated records will become list-columns of data frames.

### Larger datasets

In my timings, this code takes around 1 minute per 100 MB of data. If you need to download considerably more than this, I recommend:

- Export a `.csv` file to Cloud Storage using `bq_table_save()`.

- Use the `gsutil` command line utility to download it.
- Read the csv file into R with `readr::read_csv()` or `data.table::fread()`.

Unfortunately you can not export nested or repeated formats into CSV, and the formats that BigQuery supports (`arvn` and `ndjson`) that allow for nested/repeated values, are not well supported in R.

### Google BigQuery API documentation

- [list](#)

### Examples

```
if (bq_testable()) {
  df <- bq_table_download("publicdata.samples.natality", n_max = 35000)
}
```

---

bq\_token

*Produce configured token*

---

### Description

For internal use or for those programming around the BigQuery API. Returns a token pre-processed with `httr::config()`. Most users do not need to handle tokens "by hand" or, even if they need some control, `bq_auth()` is what they need. If there is no current token, `bq_auth()` is called to either load from cache or initiate OAuth2.0 flow. If auth has been deactivated via `bq_deauth()`, `bq_token()` returns NULL.

### Usage

```
bq_token()
```

### Value

A request object (an S3 class provided by `httr`).

### See Also

Other low-level API functions: `bq_has_token()`

### Examples

```
## Not run:
bq_token()

## End(Not run)
```

---

bq_user	<i>Get info on current user</i>
---------	---------------------------------

---

**Description**

Reveals the email address of the user associated with the current token. If no token has been loaded yet, this function does not initiate auth.

**Usage**

```
bq_user()
```

**Value**

An email address or, if no token has been loaded, NULL.

**See Also**

[gargle::token\\_userinfo\(\)](#), [gargle::token\\_email\(\)](#), [gargle::token\\_tokeninfo\(\)](#)

**Examples**

```
## Not run:
bq_user()

## End(Not run)
```

---

src_bigquery	<i>A BigQuery data source for dplyr.</i>
--------------	--

---

**Description**

Create the connection to the database with `DBI::dbConnect()` then use `dplyr::tbl()` to connect to tables within that database. Generally, it's best to provide the fully qualified name of the table (i.e. `project.dataset.table`) but if you supply a default dataset in the connection, you can use just the table name. (This, however, will prevent you from making joins across datasets.)

**Usage**

```
src_bigquery(project, dataset, billing = project, max_pages = 10)
```

**Arguments**

project	project id or name
dataset	dataset name
billing	billing project, if different to project
max_pages	(IGNORED) maximum pages returned by a query

**Examples**

```
## Not run:
library(dplyr)

# To run this example, replace billing with the id of one of your projects
# set up for billing
con <- DBI::dbConnect(bigquery(), project = bq_test_project())

shakespeare <- con %>% tbl("publicdata.samples.shakespeare")
shakespeare
shakespeare %>%
  group_by(word) %>%
  summarise(n = sum(word_count, na.rm = TRUE)) %>%
  arrange(desc(n))

## End(Not run)
```

# Index

## \* auth functions

bq\_auth, 9  
bq\_auth\_configure, 11  
bq\_deauth, 13

## \* low-level API functions

bq\_has\_token, 14  
bq\_token, 20

api-dataset, 2, 18

api-job, 4, 18

api-perform, 4, 18

api-project, 5

api-table, 6, 18

as.data.frame(), 19

as\_bq\_dataset (bq\_refs), 17

as\_bq\_field (bq\_field), 13

as\_bq\_fields (bq\_field), 13

as\_bq\_job (bq\_refs), 17

as\_bq\_table (bq\_refs), 17

bigquery, 8

bit64::integer64, 8, 19

bq\_auth, 9, 12, 13

bq\_auth(), 11, 13, 20

bq\_auth\_configure, 11, 11, 13

bq\_auth\_configure(), 11

bq\_dataset, 3, 5, 16

bq\_dataset (bq\_refs), 17

bq\_dataset\_create (api-dataset), 2

bq\_dataset\_delete (api-dataset), 2

bq\_dataset\_exists (api-dataset), 2

bq\_dataset\_meta (api-dataset), 2

bq\_dataset\_query (bq\_query), 15

bq\_dataset\_tables (api-dataset), 2

bq\_dataset\_update (api-dataset), 2

bq\_deauth, 11, 12, 13

bq\_deauth(), 20

bq\_field, 13

bq\_fields, 6, 7

bq\_fields (bq\_field), 13

bq\_has\_token, 14, 20

bq\_job, 4, 5

bq\_job (bq\_refs), 17

bq\_job\_meta (api-job), 4

bq\_job\_show\_statistics (api-job), 4

bq\_job\_status (api-job), 4

bq\_job\_wait (api-job), 4

bq\_job\_wait(), 15

bq\_oauth\_app (bq\_auth\_configure), 11

bq\_perform\_query(), 15, 16

bq\_project\_datasets (api-project), 5

bq\_project\_jobs (api-project), 5

bq\_project\_query (bq\_query), 15

bq\_projects, 15

bq\_query, 15

bq\_refs, 17

bq\_table, 6, 7, 15, 16, 19

bq\_table (bq\_refs), 17

bq\_table\_copy (api-table), 6

bq\_table\_create (api-table), 6

bq\_table\_delete (api-table), 6

bq\_table\_download, 18

bq\_table\_exists (api-table), 6

bq\_table\_fields (api-table), 6

bq\_table\_load (api-table), 6

bq\_table\_meta (api-table), 6

bq\_table\_nrow (api-table), 6

bq\_table\_patch (api-table), 6

bq\_table\_save (api-table), 6

bq\_table\_save(), 19

bq\_table\_size (api-table), 6

bq\_table\_upload (api-table), 6

bq\_token, 14, 20

bq\_user, 21

dbConnect, BigQueryDriver-method  
(bigquery), 8

DBI::dbConnect(), 8

dbi\_driver (bigquery), 8

DBIConnection, 8

DBIDriver, [8](#)  
dplyr::tbl(), [21](#)

gargle::AuthState, [12](#)  
gargle::gargle\_options, [11](#)  
gargle::token\_email(), [21](#)  
gargle::token\_fetch(), [9, 11, 13](#)  
gargle::token\_tokeninfo(), [21](#)  
gargle::token\_userinfo(), [21](#)  
gargle\_oauth\_cache(), [10](#)  
gargle\_oauth\_email(), [10](#)  
gargle\_oob\_default(), [10](#)

httr, [20](#)  
httr::config(), [10, 20](#)  
httr::oauth\_app(), [12](#)

jsonlite::fromJSON(), [10, 12](#)

src\_bigquery, [21](#)

Token2.0, [10, 11](#)