

Package ‘ggstatsplot’

May 27, 2022

Type Package

Title 'ggplot2' Based Plots with Statistical Details

Version 0.9.3

Maintainer Indrajeet Patil <patilindrajeet.science@gmail.com>

Description Extension of 'ggplot2', 'ggstatsplot' creates graphics with details from statistical tests included in the plots themselves. It provides an easier syntax to generate information-rich plots for statistical analysis of continuous (violin plots, scatterplots, histograms, dot plots, dot-and-whisker plots) or categorical (pie and bar charts) data. Currently, it supports the most common types of statistical approaches and tests: parametric, nonparametric, robust, and Bayesian versions of t-test/ANOVA, correlation analyses, contingency table analysis, meta-analysis, and regression analyses.

License GPL-3 | file LICENSE

URL <https://indrajeetpatil.github.io/ggstatsplot/>,
<https://github.com/IndrajeetPatil/ggstatsplot>

BugReports <https://github.com/IndrajeetPatil/ggstatsplot/issues>

Depends R (>= 4.0.0)

Imports correlation (>= 0.8.1), dplyr, ggplot2, ggrepel, ggsignif, glue, insight (>= 0.17.1), paletteer, parameters (>= 0.18.0), patchwork, performance, purrr, rlang, stats, statsExpressions (>= 1.3.2), tidyr, utils

Suggests afex, BayesFactor (>= 0.9.12-4.3), gapminder, ggcorrplot, ggside, knitr, lme4, MASS, metaBMA, metafor, PMCMRplus, psych, rmarkdown, spelling, survival, testthat (>= 3.1.4), tibble, vdiff, WRS2

VignetteBuilder knitr

Encoding UTF-8

Language en-US

LazyData true

RoxygenNote 7.2.0

Config/testthat/edition 3

Config/testthat/parallel true

NeedsCompilation no

Author Indrajeet Patil [cre, aut, cph]
(<<https://orcid.org/0000-0003-1995-6531>>, @patilindrajeets)

Repository CRAN

Date/Publication 2022-05-27 10:00:02 UTC

R topics documented:

ggstatsplot-package	3
bugs_long	4
bugs_wide	5
combine_plots	6
extract_stats	7
ggbarstats	8
ggbetweenstats	12
ggcoefstats	17
ggcorrmat	20
ggdotplotstats	23
gghistostats	26
ggpiestats	29
ggscatterstats	33
ggwithinstats	36
grouped_ggbarstats	41
grouped_ggbetweenstats	44
grouped_ggcorrmat	49
grouped_ggdotplotstats	52
grouped_gghistostats	55
grouped_ggpiestats	58
grouped_ggscatterstats	61
grouped_ggwithinstats	64
iris_long	68
movies_long	69
theme_ggstatsplot	70
Titanic_full	70

Index 72

ggstatsplot-package *ggstatsplot: 'ggplot2' Based Plots with Statistical Details*

Description

`{ggstatsplot}` is an extension of `{ggplot2}` package. It creates graphics with details from statistical tests included in the plots themselves. It provides an easier API to generate information-rich plots for statistical analysis of continuous (violin plots, scatterplots, histograms, dot plots, dot-and-whisker plots) or categorical (pie and bar charts) data. Currently, it supports the most common types of statistical tests: parametric, nonparametric, robust, and Bayesian versions of *t*-test/ANOVA, correlation analyses, contingency table analysis, meta-analysis, and regression analyses.

Details

`ggstatsplot`

The main functions are:

- `ggbetweenstats()` function to produce information-rich comparison plot *between* different groups or conditions with `{ggplot2}` and details from the statistical tests in the subtitle.
- `ggwithinstats()` function to produce information-rich comparison plot *within* different groups or conditions with `{ggplot2}` and details from the statistical tests in the subtitle.
- `ggscatterstats()` function to produce `{ggplot2}` scatterplots along with a marginal distribution plots from `{ggside}` package and details from the statistical tests in the subtitle.
- `ggpiestats()` function to produce pie chart with details from the statistical tests in the subtitle.
- `ggbarstats()` function to produce stacked bar chart with details from the statistical tests in the subtitle.
- `gghistostats()` function to produce histogram for a single variable with results from one sample test displayed in the subtitle.
- `ggdotplotstats()` function to produce Cleveland-style dot plots/charts for a single variable with labels and results from one sample test displayed in the subtitle.
- `ggcorrmat()` function to visualize the correlation matrix.
- `ggcoefstats()` function to visualize results from regression analyses.
- `combine_plots()` helper function to combine multiple `{ggstatsplot}` plots using `patchwork::wrap_plots()`.

For more documentation, see the dedicated [Website](#).

Author(s)

Maintainer: Indrajeet Patil <patilindrajeet.science@gmail.com> ([ORCID](#)) (@patilindrajeets)
[copyright holder]

See Also

Useful links:

- <https://indrajeetpatil.github.io/ggstatsplot/>
- <https://github.com/IndrajeetPatil/ggstatsplot>
- Report bugs at <https://github.com/IndrajeetPatil/ggstatsplot/issues>

bugs_long

Tidy version of the "Bugs" dataset.

Description

Tidy version of the "Bugs" dataset.

Usage

```
bugs_long
```

Format

A data frame with 372 rows and 6 variables

- subject. Dummy identity number for each participant.
- gender. Participant's gender (Female, Male).
- region. Region of the world the participant was from.
- education. Level of education.
- condition. Condition of the experiment the participant gave rating for (**LDLF**: low frighteningness and low disgustingness; **LFHD**: low frighteningness and high disgustingness; **HFHD**: high frighteningness and low disgustingness; **HFHD**: high frighteningness and high disgustingness).
- desire. The desire to kill an arthropod was indicated on a scale from 0 to 10.

Details

This data set, "Bugs", provides the extent to which men and women want to kill arthropods that vary in frighteningness (low, high) and disgustingness (low, high). Each participant rates their attitudes towards all arthropods. Subset of the data reported by Ryan et al. (2013).

Source

<https://www.sciencedirect.com/science/article/pii/S0747563213000277>

Examples

```
dim(bugs_long)
head(bugs_long)
dplyr::glimpse(bugs_long)
```

`bugs_wide`*Wide-format version of the "Bugs" dataset.*

Description

Wide-format version of the "Bugs" dataset.

Usage

```
bugs_wide
```

Format

A data frame with 93 rows and 6 variables

- `subject`. Dummy identity number for each participant.
- `gender`. Participant's gender (Female, Male).
- `region`. Region of the world the participant was from.
- `education`. Level of education.
- `ldlf,ldhf,hdlf,hdhf`. The desire to kill an arthropod was indicated on a scale from 0 to 10 in each condition of the experiment (**LDLF**: low frighteningness and low disgustingness; **LFHD**: low frighteningness and high disgustingness; **HFHD**: high frighteningness and low disgustingness; **HFHD**: high frighteningness and high disgustingness).

Details

This data set, "Bugs", provides the extent to which men and women want to kill arthropods that vary in frighteningness (low, high) and disgustingness (low, high). Each participant rates their attitudes towards all arthropods. Subset of the data reported by Ryan et al. (2013).

Source

<https://www.sciencedirect.com/science/article/pii/S0747563213000277>

Examples

```
dim(bugs_wide)
head(bugs_wide)
dplyr::glimpse(bugs_wide)
```

 combine_plots

Combining and arranging multiple plots in a grid

Description

Wrapper around `patchwork::wrap_plots` that will return a combined grid of plots with annotations. In case you want to create a grid of plots, it is **highly recommended** that you use `{patchwork}` package directly and not this wrapper around it which is mostly useful with `{ggstatsplot}` plots. It is exported only for backward compatibility.

Usage

```
combine_plots(
  plotlist,
  plotgrid.args = list(),
  annotation.args = list(),
  guides = "collect",
  ...
)
```

Arguments

<code>plotlist</code>	A list containing <code>ggplot</code> objects.
<code>plotgrid.args</code>	A list of additional arguments passed to <code>patchwork::wrap_plots</code> , except for <code>guides</code> argument which is already separately specified here.
<code>annotation.args</code>	A list of additional arguments passed to <code>patchwork::plot_annotation</code> .
<code>guides</code>	A string specifying how guides should be treated in the layout. 'collect' will collect guides below to the given nesting level, removing duplicates. 'keep' will stop collection at this level and let guides be placed alongside their plot. <code>auto</code> will allow guides to be collected if a upper level tries, but place them alongside the plot if not. If you modify default guide "position" with theme(legend.position=...) while also collecting guides you must apply that change to the overall <code>patchwork</code> (see example).
<code>...</code>	Currently ignored.

Value

Combined plot with annotation labels

Examples

```
# loading the necessary libraries
library(ggplot2)

# preparing the first plot
p1 <- ggplot(
```

```
data = subset(iris, iris$Species == "setosa"),
aes(x = Sepal.Length, y = Sepal.Width)
) +
geom_point() +
labs(title = "setosa")

# preparing the second plot
p2 <- ggplot(
  data = subset(iris, iris$Species == "versicolor"),
  aes(x = Sepal.Length, y = Sepal.Width)
) +
geom_point() +
labs(title = "versicolor")

# combining the plot with a title and a caption
combine_plots(
  plotlist = list(p1, p2),
  plotgrid.args = list(nrow = 1),
  annotation.args = list(
    tag_levels = "a",
    title = "Dataset: Iris Flower dataset",
    subtitle = "Edgar Anderson collected this data",
    caption = "Note: Only two species of flower are displayed",
    theme = theme(
      plot.subtitle = element_text(size = 20),
      plot.title = element_text(size = 30)
    )
  )
)
```

extract_stats

Extracting data frames from {ggstatsplot} plots

Description

Extracting data frames from {ggstatsplot} plots

Usage

```
extract_stats(p, ...)
```

Arguments

p	A plot from {ggstatsplot} package
...	Ignored

Details

This is a convenience function to extract data frames with statistical details that are used to create expressions displayed in {ggstatsplot} plots as subtitle, caption, etc. Note that all of this analysis is carried out by the {statsExpressions} [package](#).

The only exception is the ggcorrmat() function. But, if a data frame is what you want, you shouldn't be using ggcorrmat() anyway. You can use correlation::correlation() function which provides tidy data frames by default. This also works if the data entered is grouped (*a la* dplyr::group_by()). This is also the function used internally by {ggstatsplot} to extract a data frame used to create a plot.

Value

A list of tibbles containing summaries of various statistical analyses.

Examples

```
if (require("PMCMRplus")) {
  set.seed(123)
  library(ggstatsplot)

  # in case of group comparisons
  p <- ggbetweenstats(mtcars, cyl, mpg)
  extract_stats(p)

  # the exact details depend on the function
  extract_stats(ggbarstats(mtcars, cyl, am))
}
```

ggbarstats

Stacked bar charts with statistical tests

Description

Bar charts for categorical data with statistical details included in the plot as a subtitle.

Usage

```
ggbarstats(
  data,
  x,
  y,
  counts = NULL,
  type = "parametric",
  paired = FALSE,
  results.subtitle = TRUE,
  label = "percentage",
```



```

label.args = list(alpha = 1, fill = "white"),
k = 2L,
proportion.test = results.subtitle,
perc.k = 0L,
bf.message = TRUE,
ratio = NULL,
conf.level = 0.95,
sampling.plan = "indepMulti",
fixed.margin = "rows",
prior.concentration = 1,
title = NULL,
subtitle = NULL,
caption = NULL,
legend.title = NULL,
xlab = NULL,
ylab = NULL,
ggtheme = ggstatsplot::theme_ggstatsplot(),
package = "RColorBrewer",
palette = "Dark2",
ggplot.component = NULL,
output = "plot",
...
)

```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	The variable to use as the rows in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
y	The variable to use as the columns in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.
counts	The variable in data containing counts, or NULL if each row represents a single observation.
type	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>

<code>paired</code>	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<code>label</code>	Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
<code>label.args</code>	Additional aesthetic arguments that will be passed to <code>geom_label</code> .
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>proportion.test</code>	Decides whether proportion test for <code>x</code> variable is to be carried out for each level of <code>y</code> . Defaults to <code>results.subtitle</code> . In <code>ggbarstats</code> , only p -values from this test will be displayed.
<code>perc.k</code>	Numeric that decides number of decimal places for percentage labels (Default: <code>0L</code>).
<code>bf.message</code>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
<code>ratio</code>	A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be <code>ratio = c(0.5, 0.5)</code> or if there are four levels this will be <code>ratio = c(0.25, 0.25, 0.25, 0.25)</code> , etc.
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>sampling.plan</code>	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingencyTableBF()</code> .
<code>fixed.margin</code>	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
<code>prior.concentration</code>	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>legend.title</code>	Title text for the legend.
<code>xlab</code>	Label for <code>x</code> axis variable. If NULL (default), variable name for <code>x</code> will be used.
<code>ylab</code>	Labels for <code>y</code> axis variable. If NULL (default), variable name for <code>y</code> will be used.

ggtheme	A {ggplot2} theme. Default value is ggstatsplot::theme_ggstatsplot(). Any of the {ggplot2} themes (e.g., theme_bw()), or themes from extension packages are allowed (e.g., ggthemes::theme_fivethirtyeight(), hrbrthemes::theme_ipsum_ps() etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, ggbetweenstats() shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. ggthemes::theme_fivethirtyeight()) will remove the secondary Y-axis and thus the details as well.
package, palette	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running View(paletter::palettes_d_names).
ggplot.component	A ggplot component to be added to the plot prepared by {ggstatsplot}. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a {ggplot2} function or a list of {ggplot2} functions.
output	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set results.subtitle = FALSE, then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when type = "parametric" and bf.message = TRUE, otherwise this will return a NULL.
...	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html

See Also

[grouped_ggbarstats](#), [ggpiestats](#), [grouped_ggpiestats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)

# association test (or contingency table analysis)
ggbarstats(mtcars, x = vs, y = cyl)
```

 ggbetweenstats

Box/Violin plots for between-subjects comparisons

Description

A combination of box and violin plots along with jittered data points for between-subjects designs with statistical details included in the plot as a subtitle.

Usage

```
ggbetweenstats(
  data,
  x,
  y,
  plot.type = "boxviolin",
  type = "parametric",
  pairwise.comparisons = TRUE,
  pairwise.display = "significant",
  p.adjust.method = "holm",
  effsize.type = "unbiased",
  bf.prior = 0.707,
  bf.message = TRUE,
  results.subtitle = TRUE,
  xlab = NULL,
  ylab = NULL,
  caption = NULL,
  title = NULL,
  subtitle = NULL,
  k = 2L,
  var.equal = FALSE,
  conf.level = 0.95,
  nboot = 100L,
  tr = 0.2,
  centrality.plotting = TRUE,
  centrality.type = type,
  centrality.point.args = list(size = 5, color = "darkred"),
  centrality.label.args = list(size = 3, nudge_x = 0.4, segment.linetype = 4,
    min.segment.length = 0),
  outlier.tagging = FALSE,
  outlier.label = NULL,
  outlier.coef = 1.5,
  outlier.shape = 19,
  outlier.color = "black",
  outlier.label.args = list(size = 3),
  point.args = list(position = ggplot2::position_jitterdodge(dodge.width = 0.6), alpha
    = 0.4, size = 3, stroke = 0),
  violin.args = list(width = 0.5, alpha = 0.2),
```

```

ggsignif.args = list(textsize = 3, tip_length = 0.01),
ggtheme = ggstatsplot::theme_ggstatsplot(),
package = "RColorBrewer",
palette = "Dark2",
ggplot.component = NULL,
output = "plot",
...
)

```

Arguments

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., <code>matrix</code> , <code>table</code> , <code>array</code> , etc.) will not be accepted. Additionally, grouped data frames from <code>{dplyr}</code> should be ungrouped before they are entered as data.
<code>x</code>	The grouping (or independent) variable from data. In case of a repeated measures or within-subjects design, if <code>subject.id</code> argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is not sorted, the results <i>can</i> be inaccurate when there are more than two levels in <code>x</code> and there are NAs present. The data is expected to be sorted by user in <code>subject-1, subject-2, ..., pattern</code> .
<code>y</code>	The response (or outcome or dependent) variable from data.
<code>plot.type</code>	Character describing the <i>type</i> of plot. Currently supported plots are "box" (for only boxplots), "violin" (for only violin plots), and "boxviolin" (for a combination of box and violin plots; default).
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>
<code>pairwise.comparisons</code>	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only significant comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwise_comparisons</code> function. For more details about pairwise comparisons, see the documentation for that function.
<code>pairwise.display</code>	Decides <i>which</i> pairwise comparisons to display. Available options are: <ul style="list-style-type: none"> • "significant" (abbreviation accepted: "s") • "non-significant" (abbreviation accepted: "ns") • "all"

You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.

p.adjust.method	Adjustment method for p -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
effsize.type	Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, sqrt(2)/2, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
xlab	Label for x axis variable. If NULL (default), variable name for x will be used.
ylab	Labels for y axis variable. If NULL (default), variable name for y will be used.
caption	The text for the plot caption. This argument is relevant only if bf.message = FALSE.
title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if results.subtitle = FALSE.
k	Number of digits after decimal point (should be an integer) (Default: k = 2L).
var.equal	a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
nboot	Number of bootstrap samples for computing confidence interval for the effect size (Default: 100L).
tr	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help.
centrality.plotting	Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument. <ul style="list-style-type: none"> • mean for parametric statistics • median for non-parametric statistics • trimmed mean for robust statistics

- **MAP estimator** for Bayesian statistics

If you want default centrality parameter, you can specify this using `centrality.type` argument.

`centrality.type`

Decides which centrality parameter is to be displayed. The default is to choose the same as `type` argument. You can specify this to be:

- "parameteric" (for **mean**)
- "nonparametric" (for **median**)
- robust (for **trimmed mean**)
- bayes (for **MAP estimator**)

Just as `type` argument, abbreviations are also accepted.

`centrality.point.args`, `centrality.label.args`

A list of additional aesthetic arguments to be passed to `geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.

`outlier.tagging`

Decides whether outliers should be tagged (Default: FALSE).

`outlier.label`

Label to put on the outliers that have been tagged. This **can't** be the same as `x` argument.

`outlier.coef`

Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) `outlier.coef` times the Inter-Quartile Range (IQR) (Default: 1.5).

`outlier.shape`

Hiding the outliers can be achieved by setting `outlier.shape = NA`. Importantly, this does not remove the outliers, it only hides them, so the range calculated for the y-axis will be the same with outliers shown and outliers hidden.

`outlier.color`

Default aesthetics for outliers (Default: "black").

`outlier.label.args`

A list of additional aesthetic arguments to be passed to `ggrepel::geom_label_repel` for outlier label plotting.

`point.args`

A list of additional aesthetic arguments to be passed to the `geom_point` displaying the raw data.

`violin.args`

A list of additional aesthetic arguments to be passed to the `geom_violin`.

`ggsignif.args`

A list of additional aesthetic arguments to be passed to `ggsignif::geom_signif`.

`ggtheme`

A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()` etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

`package`, `palette`

Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.

<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is <code>NULL</code> . The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a <code>NULL</code> . Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a <code>NULL</code> .
<code>...</code>	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggbetweenstats.html

See Also

[grouped_ggbetweenstats](#), [ggwithinstats](#), [grouped_ggwithinstats](#)

Examples

```
if (require("PMCMRplus")) {
  # to get reproducible results from bootstrapping
  set.seed(123)
  library(ggstatsplot)

  # simple function call with the defaults
  ggbetweenstats(mtcars, am, mpg)

  # more detailed function call
  ggbetweenstats(
    data = morley,
    x = Expt,
    y = Speed,
    type = "robust",
    xlab = "The experiment number",
    ylab = "Speed-of-light measurement",
    pairwise.comparisons = TRUE,
    p.adjust.method = "fdr",
    outlier.tagging = TRUE,
    outlier.label = Run
  )
}
```


Description

Plot with the regression coefficients' point estimates as dots with confidence interval whiskers and other statistical details included as labels.

Usage

```
ggcoefstats(  
  x,  
  output = "plot",  
  statistic = NULL,  
  conf.int = TRUE,  
  conf.level = 0.95,  
  k = 2L,  
  exclude.intercept = FALSE,  
  effsize = "eta",  
  meta.analytic.effect = FALSE,  
  meta.type = "parametric",  
  bf.message = TRUE,  
  sort = "none",  
  xlab = NULL,  
  ylab = NULL,  
  title = NULL,  
  subtitle = NULL,  
  caption = NULL,  
  only.significant = FALSE,  
  point.args = list(size = 3, color = "blue"),  
  errorbar.args = list(height = 0),  
  vline = TRUE,  
  vline.args = list(size = 1, linetype = "dashed"),  
  stats.labels = TRUE,  
  stats.label.color = NULL,  
  stats.label.args = list(size = 3, direction = "y", min.segment.length = 0),  
  package = "RColorBrewer",  
  palette = "Dark2",  
  ggtheme = ggstatsplot::theme_ggstatsplot(),  
  ...  
)
```

Arguments

x A model object to be tidied, or a tidy data frame containing results from a regression model. Function internally uses `parameters::model_parameters()` to get a tidy dataframe. If a dataframe is entered, it *must* contain at the minimum

	two columns named <code>term</code> (names of predictors) and <code>estimate</code> (corresponding estimates of coefficients or other quantities of interest).
<code>output</code>	Character describing the expected output from this function: <code>"plot"</code> (visualization of regression coefficients) or <code>"tidy"</code> (tidy dataframe of results parameters: <code>:model_parameters</code>) or <code>"glance"</code> (object from performance: <code>:model_performance</code>).
<code>statistic</code>	Which statistic is to be displayed (either <code>"t"</code> or <code>"f"</code> or <code>"z"</code> or <code>"chi"</code>) in the label. This is relevant if the <code>x</code> argument is a <i>dataframe</i> .
<code>conf.int</code>	Logical. Decides whether to display confidence intervals as error bars (Default: TRUE).
<code>conf.level</code>	Numeric deciding level of confidence or credible intervals (Default: 0.95).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>exclude.intercept</code>	Logical that decides whether the intercept should be excluded from the plot (Default: FALSE).
<code>effsize</code>	Character describing the effect size to be displayed: <code>"eta"</code> (default) or <code>"omega"</code> . This argument is relevant only for models objects with <i>F</i> -statistic.
<code>meta.analytic.effect</code>	Logical that decides whether subtitle for meta-analysis via linear (mixed-effects) models (default: FALSE). If TRUE, input to argument <code>subtitle</code> will be ignored. This will be mostly relevant if a data frame with estimates and their standard errors is entered.
<code>meta.type</code>	Type of statistics used to carry out random-effects meta-analysis. If <code>"parametric"</code> (default), <code>metafor::rma</code> function will be used. If <code>"robust"</code> , <code>metaplus::metaplus</code> function will be used. If <code>"bayes"</code> , <code>metaBMA::meta_random</code> function will be used.
<code>bf.message</code>	Logical that decides whether results from running a Bayesian meta-analysis assuming that the effect size <i>d</i> varies across studies with standard deviation <i>t</i> (i.e., a random-effects analysis) should be displayed in caption. Defaults to TRUE.
<code>sort</code>	If <code>"none"</code> (default) do not sort, <code>"ascending"</code> sort by increasing coefficient value, or <code>"descending"</code> sort by decreasing coefficient value.
<code>xlab</code>	Label for x axis variable. If NULL (default), variable name for x will be used.
<code>ylab</code>	Labels for y axis variable. If NULL (default), variable name for y will be used.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. The input to this argument will be ignored if <code>meta.analytic.effect</code> is set to TRUE.
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>only.significant</code>	If TRUE, only stats labels for significant effects is shown (Default: FALSE). This can be helpful when a large number of regression coefficients are to be displayed in a single plot. Relevant only when the output is a plot.
<code>point.args</code>	Additional arguments that will be passed to <code>geom_point</code> geom. Please see documentation for that function to know more about these arguments.

<code>errorbar.args</code>	Additional arguments that will be passed to <code>geom_errorbarh</code> geom. Please see documentation for that function to know more about these arguments.
<code>vline</code>	Decides whether to display a vertical line (Default: "TRUE").
<code>vline.args</code>	Additional arguments that will be passed to <code>geom_vline</code> geom. Please see documentation for that function to know more about these arguments.
<code>stats.labels</code>	Logical. Decides whether the statistic and p -values for each coefficient are to be attached to each dot as a text label using <code>ggrepel</code> (Default: TRUE).
<code>stats.label.color</code>	Color for the labels. If set to NULL, colors will be chosen from the specified package (Default: "RColorBrewer") and <code>palette</code> (Default: "Dark2").
<code>stats.label.args</code>	Additional arguments that will be passed to <code>ggrepel::geom_label_repel</code> geom. Please see documentation for that function to know more about these arguments.
<code>package, palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>ggtheme</code>	A {ggplot2} theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the {ggplot2} themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
<code>...</code>	Additional arguments to tidying method. For more, see <code>parameters::model_parameters</code> .

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcoefstats.html

Note

1. In case you want to carry out meta-analysis, you will be asked to install the needed packages (`{metafor}`, `{metapplus}`, or `{metaBMA}`) for meta-analysis (if unavailable).
2. All rows of regression estimates where either of the following quantities is NA will be removed if labels are requested: `estimate`, `statistic`, `p.value`.
3. Given the rapid pace at which new methods are added to these packages, it is recommended that you install the GitHub versions of `{parameters}` and `{performance}` in order to make most of this function.

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)
```

```
# model object
mod <- lm(formula = mpg ~ cyl * am, data = mtcars)

# to get a plot
ggcoefstats(mod, output = "plot")

# to get a tidy dataframe
ggcoefstats(mod, output = "tidy")

# to get a glance summary
ggcoefstats(mod, output = "glance")
```

ggcorrmat

Visualization of a correlation matrix

Description

Correlation matrix or a dataframe containing results from pairwise correlation tests. The package internally uses `ggcorrplot::ggcorrplot` for creating the visualization matrix, while the correlation analysis is carried out using the `correlation::correlation` function.

Usage

```
ggcorrmat(
  data,
  cor.vars = NULL,
  cor.vars.names = NULL,
  output = "plot",
  matrix.type = "upper",
  type = "parametric",
  tr = 0.2,
  partial = FALSE,
  k = 2L,
  sig.level = 0.05,
  conf.level = 0.95,
  bf.prior = 0.707,
  p.adjust.method = "holm",
  pch = "cross",
  ggcorrplot.args = list(method = "square", outline.color = "black", pch.cex = 14),
  package = "RColorBrewer",
  palette = "Dark2",
  colors = c("#E69F00", "white", "#009E73"),
  ggtheme = ggstatsplot::theme_ggstatsplot(),
  ggplot.component = NULL,
  title = NULL,
  subtitle = NULL,
```

```

    caption = NULL,
    ...
)

```

Arguments

<code>data</code>	Dataframe from which variables specified are preferentially to be taken.
<code>cor.vars</code>	List of variables for which the correlation matrix is to be computed and visualized. If <code>NULL</code> (default), all numeric variables from <code>data</code> will be used.
<code>cor.vars.names</code>	Optional list of names to be used for <code>cor.vars</code> . The names should be entered in the same order.
<code>output</code>	Character that decides expected output from this function. If <code>"plot"</code> , the visualization matrix will be returned. If <code>"dataframe"</code> (or literally anything other than <code>"plot"</code>), a dataframe containing all details from statistical analyses (e.g., correlation coefficients, statistic values, <i>p</i> -values, no. of observations, etc.) will be returned.
<code>matrix.type</code>	Character, <code>"upper"</code> (default), <code>"lower"</code> , or <code>"full"</code> , display full matrix, lower triangular or upper triangular matrix.
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • <code>"parametric"</code> • <code>"nonparametric"</code> • <code>"robust"</code> • <code>"bayes"</code> <p>You can specify just the initial letter.</p>
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to <code>0.2</code> . Lowering the value might help.
<code>partial</code>	Can be <code>TRUE</code> for partial correlations. For Bayesian partial correlations, <code>"full"</code> instead of pseudo-Bayesian partial correlations (i.e., Bayesian correlation based on frequentist partialization) are returned.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>sig.level</code>	Significance level (Default: <code>0.05</code>). If the <i>p</i> -value in <i>p</i> -value matrix is bigger than <code>sig.level</code> , then the corresponding correlation coefficient is regarded as insignificant and flagged as such in the plot. Relevant only when <code>output = "plot"</code> .
<code>conf.level</code>	Scalar between <code>0</code> and <code>1</code> . If unspecified, the defaults return 95% confidence/credible intervals (<code>0.95</code>).
<code>bf.prior</code>	A number between <code>0.5</code> and <code>2</code> (default <code>0.707</code>), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: <code>"medium"</code> , <code>"wide"</code> , and <code>"ultrawide"</code> , corresponding to <i>r</i> scale values of <code>1/2</code> , <code>sqrt(2)/2</code> , and <code>1</code> , respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.

<code>p.adjust.method</code>	Adjustment method for p -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
<code>pch</code>	Decides the point shape to be used for insignificant correlation coefficients (only valid when <code>insig = "pch"</code>). Default: <code>pch = "cross"</code> .
<code>ggcorrplot.args</code>	A list of additional (mostly aesthetic) arguments that will be passed to <code>ggcorrplot::ggcorrplot</code> function. The list should avoid any of the following arguments since they are already internally being used: <code>corr</code> , <code>method</code> , <code>p.mat</code> , <code>sig.level</code> , <code>ggtheme</code> , <code>colors</code> , <code>lab</code> , <code>pch</code> , <code>legend.title</code> , <code>digits</code> .
<code>package, palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
<code>colors</code>	A vector of 3 colors for low, mid, and high correlation values. If set to <code>NULL</code> , manual specification of colors will be turned off and 3 colors from the specified palette from package will be selected.
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is <code>NULL</code> . The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>...</code>	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcorrmat.html

See Also

[grouped_ggcorrmat](#) [ggscatterstats](#) [grouped_ggscatterstats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)

# to get a plot (assumes that `ggcorrplot` is installed)
if (require("ggcorrplot")) ggcorrmat(iris)

# to get a dataframe
ggcorrmat(
  data = ggplot2::msleep,
  cor.vars = sleep_total:bodywt,
  partial = TRUE,
  output = "dataframe"
)
```

ggdotplotstats

Dot plot/chart for labeled numeric data.

Description

A dot chart (as described by William S. Cleveland) with statistical details from one-sample test.

Usage

```
ggdotplotstats(
  data,
  x,
  y,
  xlab = NULL,
  ylab = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  type = "parametric",
  test.value = 0,
  bf.prior = 0.707,
  bf.message = TRUE,
  effsize.type = "g",
  conf.level = 0.95,
  tr = 0.2,
  k = 2L,
  results.subtitle = TRUE,
  point.args = list(color = "black", size = 3, shape = 16),
  centrality.plotting = TRUE,
  centrality.type = type,
  centrality.line.args = list(color = "blue", size = 1, linetype = "dashed"),
  ggplot.component = NULL,
```

```

ggtheme = ggstatsplot::theme_ggstatsplot(),
output = "plot",
...
)

```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	A numeric variable from the dataframe data.
y	Label or grouping variable.
xlab	Label for x axis variable. If NULL (default), variable name for x will be used.
ylab	Labels for y axis variable. If NULL (default), variable name for y will be used.
title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if results.subtitle = FALSE.
caption	The text for the plot caption. This argument is relevant only if bf.message = FALSE.
type	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>
test.value	A number indicating the true value of the mean (Default: 0).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
effsize.type	Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's d) or "g" (for Hedge's g).
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
tr	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help.
k	Number of digits after decimal point (should be an integer) (Default: k = 2L).
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.

<code>point.args</code>	A list of additional aesthetic arguments passed to <code>geom_point</code> .
<code>centrality.plotting</code>	Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the <code>type</code> argument. <ul style="list-style-type: none"> • mean for parametric statistics • median for non-parametric statistics • trimmed mean for robust statistics • MAP estimator for Bayesian statistics <p>If you want default centrality parameter, you can specify this using <code>centrality.type</code> argument.</p>
<code>centrality.type</code>	Decides which centrality parameter is to be displayed. The default is to choose the same as <code>type</code> argument. You can specify this to be: <ul style="list-style-type: none"> • "parametric" (for mean) • "nonparametric" (for median) • robust (for trimmed mean) • bayes (for MAP estimator) <p>Just as <code>type</code> argument, abbreviations are also accepted.</p>
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter.
<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggdotplotstats.html

See Also

[grouped_gghistostats](#), [gghistostats](#), [grouped_ggdotplotstats](#)

Examples

```
# for reproducibility
set.seed(123)

# plot
ggdotplotstats(
  data = ggplot2::mpg,
  x = cty,
  y = manufacturer,
  title = "Fuel economy data",
  xlab = "city miles per gallon"
)
```

gghistostats

Histogram for distribution of a numeric variable

Description

Histogram with statistical details from one-sample test included in the plot as a subtitle.

Usage

```
gghistostats(
  data,
  x,
  binwidth = NULL,
  xlab = NULL,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  type = "parametric",
  test.value = 0,
  bf.prior = 0.707,
  bf.message = TRUE,
  effsize.type = "g",
  conf.level = 0.95,
  tr = 0.2,
  k = 2L,
  ggtheme = ggstatsplot::theme_ggstatsplot(),
  results.subtitle = TRUE,
  bin.args = list(color = "black", fill = "grey50", alpha = 0.7),
  centrality.plotting = TRUE,
```

```

  centrality.type = type,
  centrality.line.args = list(color = "blue", size = 1, linetype = "dashed"),
  normal.curve = FALSE,
  normal.curve.args = list(size = 2),
  ggplot.component = NULL,
  output = "plot",
  ...
)

```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	A numeric variable from the dataframe data.
binwidth	The width of the histogram bins. Can be specified as a numeric value, or a function that calculates width from x. The default is to use the $\max(x) - \min(x) / \sqrt{N}$. You should always check this value and explore multiple widths to find the best to illustrate the stories in your data.
xlab	Label for x axis variable. If NULL (default), variable name for x will be used.
title	The text for the plot title.
subtitle	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
caption	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
type	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>
test.value	A number indicating the true value of the mean (Default: 0).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
effsize.type	Type of effect size needed for <i>parametric</i> tests. The argument can be "d" (for Cohen's d) or "g" (for Hedge's g).
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).

<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>ggtheme</code>	A {ggplot2} theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the {ggplot2} themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
<code>results.subtitle</code>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: <code>TRUE</code>). If set to <code>FALSE</code> , only the plot will be returned.
<code>bin.args</code>	A list of additional aesthetic arguments to be passed to the <code>stat_bin</code> used to display the bins. Do not specify <code>binwidth</code> argument in this list since it has already been specified using the dedicated argument.
<code>centrality.plotting</code>	<p>Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: <code>TRUE</code>). Function decides which central tendency measure to show depending on the <code>type</code> argument.</p> <ul style="list-style-type: none"> • mean for parametric statistics • median for non-parametric statistics • trimmed mean for robust statistics • MAP estimator for Bayesian statistics <p>If you want default centrality parameter, you can specify this using <code>centrality.type</code> argument.</p>
<code>centrality.type</code>	<p>Decides which centrality parameter is to be displayed. The default is to choose the same as <code>type</code> argument. You can specify this to be:</p> <ul style="list-style-type: none"> • "parameteric" (for mean) • "nonparametric" (for median) • robust (for trimmed mean) • bayes (for MAP estimator) <p>Just as <code>type</code> argument, abbreviations are also accepted.</p>
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter.
<code>normal.curve</code>	A logical value that decides whether to super-impose a normal curve using <code>stats::dnorm(mean(x), sd(x))</code> . Default is <code>FALSE</code> .
<code>normal.curve.args</code>	A list of additional aesthetic arguments to be passed to the normal curve.

<code>ggplot.component</code>	A ggplot component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is <code>NULL</code> . The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a <code>NULL</code> . Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a <code>NULL</code> .
<code>...</code>	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/gghistostats.html

See Also

[grouped_gghistostats](#), [ggdotplotstats](#), [grouped_ggdotplotstats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)

# using defaults, but modifying which centrality parameter is to be shown
gghistostats(
  data      = ToothGrowth,
  x         = len,
  xlab      = "Tooth length",
  centrality.type = "np"
)
```

Description

Pie charts for categorical data with statistical details included in the plot as a subtitle.

Usage

```

ggpiestats(
  data,
  x,
  y = NULL,
  counts = NULL,
  type = "parametric",
  paired = FALSE,
  results.subtitle = TRUE,
  label = "percentage",
  label.args = list(direction = "both"),
  label.repel = FALSE,
  k = 2L,
  proportion.test = results.subtitle,
  perc.k = 0L,
  bf.message = TRUE,
  ratio = NULL,
  conf.level = 0.95,
  sampling.plan = "indepMulti",
  fixed.margin = "rows",
  prior.concentration = 1,
  title = NULL,
  subtitle = NULL,
  caption = NULL,
  legend.title = NULL,
  ggtheme = ggstatsplot::theme_ggstatsplot(),
  package = "RColorBrewer",
  palette = "Dark2",
  ggplot.component = NULL,
  output = "plot",
  ...
)

```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	The variable to use as the rows in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
y	The variable to use as the columns in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for ggbarstats function.
counts	The variable in data containing counts, or NULL if each row represents a single observation.

type	<p>A character specifying the type of statistical approach:</p> <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>
paired	Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test expression will be returned. If FALSE, Pearson's chi-square test will be returned.
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
label	Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
label.args	Additional aesthetic arguments that will be passed to <code>geom_label</code> .
label.repel	Whether labels should be repelled using <code>ggrepel</code> package. This can be helpful in case the labels are overlapping.
k	Number of digits after decimal point (should be an integer) (Default: $k = 2L$).
proportion.test	Decides whether proportion test for x variable is to be carried out for each level of y . Defaults to <code>results.subtitle</code> . In <code>ggbarstats</code> , only p -values from this test will be displayed.
perc.k	Numeric that decides number of decimal places for percentage labels (Default: $0L$).
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
ratio	A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be <code>ratio = c(0.5, 0.5)</code> or if there are four levels this will be <code>ratio = c(0.25, 0.25, 0.25, 0.25)</code> , etc.
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
sampling.plan	Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingencyTableBF()</code> .
fixed.margin	For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
prior.concentration	Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
title	The text for the plot title.

subtitle	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
caption	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
legend.title	Title text for the legend.
ggtheme	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
package, palette	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletter::palettes_d_names)</code> .
ggplot.component	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is <code>NULL</code> . The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
output	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a <code>NULL</code> . Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a <code>NULL</code> .
...	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html

See Also

[grouped_ggpiestats](#), [ggbarstats](#), [grouped_ggbarstats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)

# one sample goodness of fit proportion test
ggpiestats(mtcars, x = vs)

# association test (or contingency table analysis)
```



```
ggpiestats(mtcars, x = vs, y = cyl)
```

ggscatterstats

Scatterplot with marginal distributions and statistical results

Description

Scatterplots from {ggplot2} combined with marginal densigram (density + histogram) plots with statistical details.

Usage

```
ggscatterstats(  
  data,  
  x,  
  y,  
  type = "parametric",  
  conf.level = 0.95,  
  bf.prior = 0.707,  
  bf.message = TRUE,  
  tr = 0.2,  
  k = 2L,  
  results.subtitle = TRUE,  
  label.var = NULL,  
  label.expression = NULL,  
  marginal = TRUE,  
  xfill = "#009E73",  
  yfill = "#D55E00",  
  point.args = list(size = 3, alpha = 0.4, stroke = 0, na.rm = TRUE),  
  point.width.jitter = 0,  
  point.height.jitter = 0,  
  point.label.args = list(size = 3, max.overlaps = 1e+06),  
  smooth.line.args = list(size = 1.5, color = "blue", method = "lm", formula = y ~ x,  
    na.rm = TRUE),  
  xsidehistogram.args = list(fill = xfill, color = "black", na.rm = TRUE),  
  ysidehistogram.args = list(fill = yfill, color = "black", na.rm = TRUE),  
  xlab = NULL,  
  ylab = NULL,  
  title = NULL,  
  subtitle = NULL,  
  caption = NULL,  
  ggtheme = ggstatsplot::theme_ggstatsplot(),  
  ggplot.component = NULL,  
  output = "plot",  
  ...  
)
```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
x	The column in data containing the explanatory variable to be plotted on the x-axis.
y	The column in data containing the response (outcome) variable to be plotted on the y-axis.
type	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
tr	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help.
k	Number of digits after decimal point (should be an integer) (Default: k = 2L).
results.subtitle	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
label.var	Variable to use for points labels entered as a symbol (e.g. var1).
label.expression	An expression evaluating to a logical vector that determines the subset of data points to label (e.g. $y < 4$ & $z < 20$). While using this argument with <code>purrr::pmap</code> , you will have to provide a quoted expression (e.g. <code>quote(y < 4 & z < 20)</code>).
marginal	Decides whether marginal distributions will be plotted on axes using <code>ggside</code> functions. The default is TRUE. The package <code>ggside</code> must already be installed by the user.
xfill, yfill	Character describing color fill for x and y axes marginal distributions (default: "#009E73" (for x) and "#D55E00" (for y)). Note that the defaults are colorblind-friendly.

<code>point.args</code>	A list of additional aesthetic arguments to be passed to <code>geom_point</code> geom used to display the raw data points.
<code>point.width.jitter</code> , <code>point.height.jitter</code>	Degree of jitter in x and y direction, respectively. Defaults to 0 (0%) of the resolution of the data. Note that the jitter should not be specified in the <code>point.args</code> because this information will be passed to two different geoms: one displaying the points and the other displaying the labels for these points.
<code>point.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> geom used to display the labels.
<code>smooth.line.args</code>	A list of additional aesthetic arguments to be passed to <code>geom_smooth</code> geom used to display the regression line.
<code>xsidehistogram.args</code> , <code>ysidehistogram.args</code>	A list of arguments passed to respective <code>geom_s</code> from <code>ggside</code> package to change the marginal distribution histograms plots.
<code>xlab</code>	Label for x axis variable. If NULL (default), variable name for x will be used.
<code>ylab</code>	Labels for y axis variable. If NULL (default), variable name for y will be used.
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggscatterstats.html

Note

The plot uses `ggrepel::geom_label_repel` to attempt to keep labels from over-lapping to the largest degree possible. As a consequence plot times will slow down massively (and the plot file will grow in size) if you have a lot of labels that overlap.

See Also

[grouped_ggscatterstats](#), [ggcorrmat](#), [grouped_ggcorrmat](#)

Examples

```
# to get reproducible results from bootstrapping
set.seed(123)
library(ggstatsplot)
library(dplyr, warn.conflicts = FALSE)

# creating dataframe with rownames converted to a new column
mtcars_new <- as_tibble(mtcars, rownames = "car")

# simple function call with the defaults
if (require("ggside")) {
  ggscatterstats(
    data = mtcars_new,
    x = wt,
    y = mpg,
    label.var = car,
    label.expression = wt < 4 & mpg < 20
  ) + # making further customization with `{ggplot2}` functions
    geom_rug(sides = "b")
}
```

 ggwithinstats

Box/Violin plots for repeated measures comparisons

Description

A combination of box and violin plots along with raw (unjittered) data points for within-subjects designs with statistical details included in the plot as a subtitle.

Usage

```
ggwithinstats(
  data,
  x,
  y,
  type = "parametric",
  pairwise.comparisons = TRUE,
  pairwise.display = "significant",
```

```

p.adjust.method = "holm",
effsize.type = "unbiased",
bf.prior = 0.707,
bf.message = TRUE,
results.subtitle = TRUE,
xlab = NULL,
ylab = NULL,
caption = NULL,
title = NULL,
subtitle = NULL,
k = 2L,
conf.level = 0.95,
nboot = 100L,
tr = 0.2,
centrality.plotting = TRUE,
centrality.type = type,
centrality.point.args = list(size = 5, color = "darkred"),
centrality.label.args = list(size = 3, nudge_x = 0.4, segment.linetype = 4),
centrality.path = TRUE,
centrality.path.args = list(size = 1, color = "red", alpha = 0.5),
point.args = list(size = 3, alpha = 0.5),
point.path = TRUE,
point.path.args = list(alpha = 0.5, linetype = "dashed"),
outlier.tagging = FALSE,
outlier.label = NULL,
outlier.coef = 1.5,
outlier.label.args = list(size = 3),
boxplot.args = list(width = 0.2, alpha = 0.5),
violin.args = list(width = 0.5, alpha = 0.2),
ggsignif.args = list(textsize = 3, tip_length = 0.01),
ggtheme = ggstatsplot::theme_ggstatsplot(),
package = "RColorBrewer",
palette = "Dark2",
ggplot.component = NULL,
output = "plot",
...
)

```

Arguments

- | | |
|------|--|
| data | A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data. |
| x | The grouping (or independent) variable from data. In case of a repeated measures or within-subjects design, if subject.id argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is |

	not sorted, the results <i>can</i> be inaccurate when there are more than two levels in <i>x</i> and there are NAs present. The data is expected to be sorted by user in subject-1,subject-2, ..., pattern.
<i>y</i>	The response (or outcome or dependent) variable from data.
<i>type</i>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>
<i>pairwise.comparisons</i>	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only significant comparisons will be shown by default. To change this behavior, select appropriate option with <i>pairwise.display</i> argument. The pairwise comparison dataframes are prepared using the <i>pairwise_comparisons</i> function. For more details about pairwise comparisons, see the documentation for that function.
<i>pairwise.display</i>	Decides <i>which</i> pairwise comparisons to display. Available options are: <ul style="list-style-type: none"> • "significant" (abbreviation accepted: "s") • "non-significant" (abbreviation accepted: "ns") • "all" <p>You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.</p>
<i>p.adjust.method</i>	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
<i>effsize.type</i>	Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
<i>bf.prior</i>	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to <i>r</i> scale values of 1/2, sqrt(2)/2, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
<i>bf.message</i>	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).
<i>results.subtitle</i>	Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
<i>xlab</i>	Label for <i>x</i> axis variable. If NULL (default), variable name for <i>x</i> will be used.
<i>ylab</i>	Labels for <i>y</i> axis variable. If NULL (default), variable name for <i>y</i> will be used.

<code>caption</code>	The text for the plot caption. This argument is relevant only if <code>bf.message = FALSE</code> .
<code>title</code>	The text for the plot title.
<code>subtitle</code>	The text for the plot subtitle. Will work only if <code>results.subtitle = FALSE</code> .
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).
<code>conf.level</code>	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
<code>nboot</code>	Number of bootstrap samples for computing confidence interval for the effect size (Default: <code>100L</code>).
<code>tr</code>	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
<code>centrality.plotting</code>	<p>Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: <code>TRUE</code>). Function decides which central tendency measure to show depending on the <code>type</code> argument.</p> <ul style="list-style-type: none"> • mean for parametric statistics • median for non-parametric statistics • trimmed mean for robust statistics • MAP estimator for Bayesian statistics <p>If you want default centrality parameter, you can specify this using <code>centrality.type</code> argument.</p>
<code>centrality.type</code>	<p>Decides which centrality parameter is to be displayed. The default is to choose the same as <code>type</code> argument. You can specify this to be:</p> <ul style="list-style-type: none"> • "parameteric" (for mean) • "nonparametric" (for median) • robust (for trimmed mean) • bayes (for MAP estimator) <p>Just as <code>type</code> argument, abbreviations are also accepted.</p>
<code>centrality.point.args</code> , <code>centrality.label.args</code>	A list of additional aesthetic arguments to be passed to <code>geom_point</code> and <code>ggrepel::geom_label_repel</code> geoms, which are involved in mean plotting.
<code>centrality.path.args</code> , <code>point.path.args</code>	A list of additional aesthetic arguments passed on to <code>geom_path</code> connecting raw data points and mean points.
<code>point.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_point</code> displaying the raw data.
<code>point.path</code> , <code>centrality.path</code>	<p>Logical that decides whether individual data points and means, respectively, should be connected using <code>geom_path</code>. Both default to <code>TRUE</code>. Note that <code>point.path</code> argument is relevant only when there are two groups (i.e., in case of a <i>t</i>-test). In case of large number of data points, it is advisable to set <code>point.path = FALSE</code> as these lines can overwhelm the plot.</p>

<code>outlier.tagging</code>	Decides whether outliers should be tagged (Default: FALSE).
<code>outlier.label</code>	Label to put on the outliers that have been tagged. This can't be the same as <code>x</code> argument.
<code>outlier.coef</code>	Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) <code>outlier.coef</code> times the Inter-Quartile Range (IQR) (Default: 1.5).
<code>outlier.label.args</code>	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> for outlier label plotting.
<code>boxplot.args</code>	A list of additional aesthetic arguments passed on to <code>geom_boxplot</code> .
<code>violin.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_violin</code> .
<code>ggsignif.args</code>	A list of additional aesthetic arguments to be passed to <code>ggsignif::geom_signif</code> .
<code>ggtheme</code>	A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
<code>package, palette</code>	Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running <code>View(paletteer::palettes_d_names)</code> .
<code>ggplot.component</code>	A <code>ggplot</code> component to be added to the plot prepared by <code>{ggstatsplot}</code> . This argument is primarily helpful for <code>grouped_</code> variants of all primary functions. Default is NULL. The argument should be entered as a <code>{ggplot2}</code> function or a list of <code>{ggplot2}</code> functions.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>...</code>	Currently ignored.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggwithinstats.html

See Also

[grouped_ggbetweenstats](#), [ggbetweenstats](#), [grouped_ggwithinstats](#)

Examples

```
# setup
set.seed(123)
library(ggstatsplot)
library(dplyr, warn.conflicts = FALSE)

# two groups (*t*-test)
ggwithinstats(
  data = filter(bugs_long, condition %in% c("HDHF", "HDLF")),
  x     = condition,
  y     = desire
)

# more than two groups (anova)
library(WRS2)

ggwithinstats(
  data      = WineTasting,
  x         = Wine,
  y         = Taste,
  type      = "r",
  outlier.tagging = TRUE,
  outlier.label = Taster
)
```

grouped_ggbarstats *Grouped bar charts with statistical tests*

Description

Helper function for `ggstatsplot::ggbarstats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

Usage

```
grouped_ggbarstats(
  data,
  ...,
  grouping.var,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list()
)
```

Arguments

- `data` A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will **not** be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
- `...` Arguments passed on to `ggbarstats`
- `x` The variable to use as the **rows** in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
 - `y` The variable to use as the **columns** in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for `ggbarstats` function.
 - `proportion.test` Decides whether proportion test for x variable is to be carried out for each level of y. Defaults to `results.subtitle`. In `ggbarstats`, only *p*-values from this test will be displayed.
 - `perc.k` Numeric that decides number of decimal places for percentage labels (Default: 0L).
 - `label` Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
 - `label.args` Additional aesthetic arguments that will be passed to `geom_label`.
 - `legend.title` Title text for the legend.
 - `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
 - `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
 - `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
 - `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
 - `ggplot.component` A ggplot component to be added to the plot prepared by {ggstatsplot}. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a {ggplot2} function or a list of {ggplot2} functions.
 - `package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.
 - `ggtheme` A {ggplot2} theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the {ggplot2} themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically

contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

`type` A character specifying the type of statistical approach:

- "parametric"
- "nonparametric"
- "robust"
- "bayes"

You can specify just the initial letter.

`k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).

`conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).

`paired` Logical indicating whether data came from a within-subjects or repeated measures design study (Default: `FALSE`). If `TRUE`, McNemar's test expression will be returned. If `FALSE`, Pearson's chi-square test will be returned.

`counts` The variable in data containing counts, or `NULL` if each row represents a single observation.

`ratio` A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is `NULL`, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be `ratio = c(0.5, 0.5)` or if there are four levels this will be `ratio = c(0.25, 0.25, 0.25, 0.25)`, etc.

`sampling.plan` Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see `?BayesFactor::contingencyTable`.

`fixed.margin` For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".

`prior.concentration` Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.

`xlab` Label for x axis variable. If `NULL` (default), variable name for x will be used.

`ylab` Labels for y axis variable. If `NULL` (default), variable name for y will be used.

`grouping.var` A single grouping variable.

`output` Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set `results.subtitle = FALSE`, then this will return a `NULL`. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when `type = "parametric"` and `bf.message = TRUE`, otherwise this will return a `NULL`.

`plotgrid.args` A list of additional arguments passed to `patchwork::wrap_plots`, except for `guides` argument which is already separately specified here.

annotation.args

A list of additional arguments passed to patchwork::plot_annotation.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html

See Also

[ggbarstats](#), [ggpiestats](#), [grouped_ggpiestats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)
library(dplyr, warn.conflicts = FALSE)

# let's create a smaller dataframe
diamonds_short <- ggplot2::diamonds %>%
  filter(cut %in% c("Very Good", "Ideal")) %>%
  filter(clarity %in% c("SI1", "SI2", "VS1", "VS2")) %>%
  sample_frac(size = 0.05)

# plot
grouped_ggbarstats(
  data      = diamonds_short,
  x         = color,
  y         = clarity,
  grouping.var = cut,
  plotgrid.args = list(nrow = 2)
)
```

grouped_ggbetweenstats

Violin plots for group or condition comparisons in between-subjects designs repeated across all levels of a grouping variable.

Description

Helper function for ggstatsplot::ggbetweenstats to apply this function across multiple levels of a given factor and combining the resulting plots using ggstatsplot::combine_plots.

Usage

```
grouped_ggbetweenstats(
  data,
  ...,
  grouping.var,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list()
)
```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
...	Arguments passed on to ggbetweenstats
plot.type	Character describing the <i>type</i> of plot. Currently supported plots are "box" (for only boxplots), "violin" (for only violin plots), and "boxviolin" (for a combination of box and violin plots; default).
xlab	Label for x axis variable. If NULL (default), variable name for x will be used.
ylab	Labels for y axis variable. If NULL (default), variable name for y will be used.
pairwise.comparisons	Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only significant comparisons will be shown by default. To change this behavior, select appropriate option with <code>pairwise.display</code> argument. The pairwise comparison dataframes are prepared using the <code>pairwise_comparisons</code> function. For more details about pairwise comparisons, see the documentation for that function.
p.adjust.method	Adjustment method for <i>p</i> -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
pairwise.display	Decides <i>which</i> pairwise comparisons to display. Available options are: <ul style="list-style-type: none"> • "significant" (abbreviation accepted: "s") • "non-significant" (abbreviation accepted: "ns") • "all" <p>You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.</p>
bf.message	Logical that decides whether to display Bayes Factor in favor of the <i>null</i> hypothesis. This argument is relevant only for parametric test (Default: TRUE).

`results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.

`subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.

`caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.

`outlier.color` Default aesthetics for outliers (Default: "black").

`outlier.tagging` Decides whether outliers should be tagged (Default: FALSE).

`outlier.label` Label to put on the outliers that have been tagged. This **can't** be the same as `x` argument.

`outlier.shape` Hiding the outliers can be achieved by setting `outlier.shape = NA`. Importantly, this does not remove the outliers, it only hides them, so the range calculated for the `y`-axis will be the same with outliers shown and outliers hidden.

`outlier.label.args` A list of additional aesthetic arguments to be passed to `ggrepel::geom_label_repel` for outlier label plotting.

`outlier.coef` Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) `outlier.coef` times the Inter-Quartile Range (IQR) (Default: 1.5).

`centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the `type` argument.

- **mean** for parametric statistics
- **median** for non-parametric statistics
- **trimmed mean** for robust statistics
- **MAP estimator** for Bayesian statistics

If you want default centrality parameter, you can specify this using `centrality.type` argument.

`centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as `type` argument. You can specify this to be:

- "parameteric" (for **mean**)
- "nonparametric" (for **median**)
- robust (for **trimmed mean**)
- bayes (for **MAP estimator**)

Just as `type` argument, abbreviations are also accepted.

`point.args` A list of additional aesthetic arguments to be passed to the `geom_point` displaying the raw data.

`violin.args` A list of additional aesthetic arguments to be passed to the `geom_violin`.

`ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

- `package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.
- `centrality.point.args,centrality.label.args` A list of additional aesthetic arguments to be passed to `geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.
- `ggsignif.args` A list of additional aesthetic arguments to be passed to `ggsignif::geom_signif`.
- `ggtheme` A {ggplot2} theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the {ggplot2} themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.
- `x` The grouping (or independent) variable from data. In case of a repeated measures or within-subjects design, if `subject.id` argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is **not** sorted, the results *can* be inaccurate when there are more than two levels in `x` and there are NAs present. The data is expected to be sorted by user in `subject-1,subject-2, ..., pattern`.
- `y` The response (or outcome or dependent) variable from data.
- `type` A character specifying the type of statistical approach:
- "parametric"
 - "nonparametric"
 - "robust"
 - "bayes"
- You can specify just the initial letter.
- `k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).
- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `effsize.type` Type of effect size needed for *parametric* tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
- `var.equal` a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to *r* scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.

	<p><code>tr</code> Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code>, which is by default set to 0.2. Lowering the value might help.</p> <p><code>nboot</code> Number of bootstrap samples for computing confidence interval for the effect size (Default: 100L).</p>
<code>grouping.var</code>	A single grouping variable.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>plotgrid.args</code>	A list of additional arguments passed to <code>patchwork::wrap_plots</code> , except for <code>guides</code> argument which is already separately specified here.
<code>annotation.args</code>	A list of additional arguments passed to <code>patchwork::plot_annotation</code> .

See Also

[ggbetweenstats](#), [ggwithinstats](#), [grouped_ggwithinstats](#)

Examples

```
if (require("PMCMRplus")) {
  # to get reproducible results from bootstrapping
  set.seed(123)
  library(ggstatsplot)
  library(dplyr, warn.conflicts = FALSE)
  library(ggplot2)

  # the most basic function call
  grouped_ggbetweenstats(
    data = filter(ggplot2::mpg, drv != "4"),
    x = year,
    y = hwy,
    grouping.var = drv
  )

  # modifying individual plots using `ggplot.component` argument
  grouped_ggbetweenstats(
    data = filter(
      movies_long,
      genre %in% c("Action", "Comedy"),
      mpaa %in% c("R", "PG")
    ),
    x = genre,
    y = rating,
    grouping.var = mpaa,
    ggplot.component = scale_y_continuous(
```



```

    breaks = seq(1, 9, 1),
    limits = (c(1, 9))
  )
)
}

```

grouped_ggcorrmat	<i>Visualization of a correlogram (or correlation matrix) for all levels of a grouping variable</i>
-------------------	---

Description

Helper function for `ggstatsplot::ggcorrmat` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

Usage

```

grouped_ggcorrmat(
  data,
  ...,
  grouping.var,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list()
)

```

Arguments

<code>data</code>	Dataframe from which variables specified are preferentially to be taken.
<code>...</code>	Arguments passed on to <code>ggcorrmat</code>
<code>cor.vars</code>	List of variables for which the correlation matrix is to be computed and visualized. If NULL (default), all numeric variables from data will be used.
<code>cor.vars.names</code>	Optional list of names to be used for <code>cor.vars</code> . The names should be entered in the same order.
<code>partial</code>	Can be TRUE for partial correlations. For Bayesian partial correlations, "full" instead of pseudo-Bayesian partial correlations (i.e., Bayesian correlation based on frequentist partialization) are returned.
<code>matrix.type</code>	Character, "upper" (default), "lower", or "full", display full matrix, lower triangular or upper triangular matrix.
<code>sig.level</code>	Significance level (Default: 0.05). If the p -value in p -value matrix is bigger than <code>sig.level</code> , then the corresponding correlation coefficient is regarded as insignificant and flagged as such in the plot. Relevant only when <code>output = "plot"</code> .

- colors** A vector of 3 colors for low, mid, and high correlation values. If set to NULL, manual specification of colors will be turned off and 3 colors from the specified palette from package will be selected.
- pch** Decides the point shape to be used for insignificant correlation coefficients (only valid when `insig = "pch"`). Default: `pch = "cross"`.
- ggcorrplot.args** A list of additional (mostly aesthetic) arguments that will be passed to `ggcorrplot::ggcorrplot` function. The list should avoid any of the following arguments since they are already internally being used: `corr`, `method`, `p.mat`, `sig.level`, `ggtheme`, `colors`, `lab`, `pch`, `legend.title`, `digits`.
- type** A character specifying the type of statistical approach:
- "parametric"
 - "nonparametric"
 - "robust"
 - "bayes"
- You can specify just the initial letter.
- k** Number of digits after decimal point (should be an integer) (Default: `k = 2L`).
- conf.level** Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- tr** Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.
- bf.prior** A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
- p.adjust.method** Adjustment method for p -values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".
- subtitle** The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- caption** The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
- ggplot.component** A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.
- package,palette** Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.
- ggtheme** A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these

themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, ggbetweenstats() shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. ggthemes::theme_fivethirtyeight()) will remove the secondary Y-axis and thus the details as well.

grouping.var	A single grouping variable.
output	Character that decides expected output from this function. If "plot", the visualization matrix will be returned. If "dataframe" (or literally anything other than "plot"), a dataframe containing all details from statistical analyses (e.g., correlation coefficients, statistic values, <i>p</i> -values, no. of observations, etc.) will be returned.
plotgrid.args	A list of additional arguments passed to patchwork::wrap_plots, except for guides argument which is already separately specified here.
annotation.args	A list of additional arguments passed to patchwork::plot_annotation.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggcorrmat.html

See Also

[ggcorrmat](#), [ggscatterstats](#), [grouped_ggscatterstats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)

# for plot
if (require("ggcorrplot")) {
  grouped_ggcorrmat(
    data = iris,
    grouping.var = Species,
    type = "robust",
    p.adjust.method = "holm",
    plotgrid.args = list(ncol = 1),
    annotation.args = list(tag_levels = "i")
  )
}

# for dataframe
grouped_ggcorrmat(
  data = ggplot2::msleep,
  grouping.var = vore,
  type = "bayes",
  output = "dataframe"
```

)

grouped_ggdotplotstats

Grouped histograms for distribution of a labeled numeric variable

Description

Helper function for `ggstatsplot::ggdotplotstats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

Usage

```
grouped_ggdotplotstats(
  data,
  ...,
  grouping.var,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list()
)
```

Arguments

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., <code>matrix</code> , <code>table</code> , <code>array</code> , etc.) will not be accepted. Additionally, grouped data frames from <code>{dplyr}</code> should be ungrouped before they are entered as data.
<code>...</code>	Arguments passed on to <code>ggdotplotstats</code>
<code>y</code>	Label or grouping variable.
<code>point.args</code>	A list of additional aesthetic arguments passed to <code>geom_point</code> .
<code>centrality.line.args</code>	A list of additional aesthetic arguments to be passed to the <code>geom_line</code> used to display the lines corresponding to the centrality parameter.
<code>x</code>	A numeric variable from the dataframe <code>data</code> .
<code>type</code>	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" You can specify just the initial letter.
<code>test.value</code>	A number indicating the true value of the mean (Default: 0).
<code>k</code>	Number of digits after decimal point (should be an integer) (Default: <code>k = 2L</code>).

- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `tr` Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
- `effsize.type` Type of effect size needed for *parametric* tests. The argument can be "d" (for Cohen's d) or "g" (for Hedge's g).
- `xlab` Label for x axis variable. If NULL (default), variable name for x will be used.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
- `centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument.
- **mean** for parametric statistics
 - **median** for non-parametric statistics
 - **trimmed mean** for robust statistics
 - **MAP estimator** for Bayesian statistics

If you want default centrality parameter, you can specify this using `centrality.type` argument.

- `centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as type argument. You can specify this to be:
- "parameteric" (for **mean**)
 - "nonparametric" (for **median**)
 - robust (for **trimmed mean**)
 - bayes (for **MAP estimator**)

Just as type argument, abbreviations are also accepted.

- `ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

	<p><code>ggtheme</code> A <code>{ggplot2}</code> theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code>. Any of the <code>{ggplot2}</code> themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code>, <code>hrbrthemes::theme_ipsum_ps()</code>, etc.). But note that sometimes these themes will remove some of the details that <code>{ggstatsplot}</code> plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.</p> <p><code>ylab</code> Labels for y axis variable. If NULL (default), variable name for y will be used.</p>
<code>grouping.var</code>	A single grouping variable.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>plotgrid.args</code>	A list of additional arguments passed to <code>patchwork::wrap_plots</code> , except for <code>guides</code> argument which is already separately specified here.
<code>annotation.args</code>	A list of additional arguments passed to <code>patchwork::plot_annotation</code> .

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggdotplotstats.html

See Also

[grouped_gghistostats](#), [ggdotplotstats](#), [gghistostats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)
library(dplyr, warn.conflicts = FALSE)

# removing factor level with very few no. of observations
df <- filter(ggplot2::mpg, cyl %in% c("4", "6", "8"))

# plot
grouped_ggdotplotstats(
  data      = df,
  x         = cty,
  y         = manufacturer,
  grouping.var = cyl,
```

```

    test.value = 15.5
  )

```

grouped_gghistostats *Grouped histograms for distribution of a numeric variable*

Description

Helper function for `ggstatsplot::gghistostats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

Usage

```

grouped_gghistostats(
  data,
  x,
  grouping.var,
  binwidth = NULL,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list(),
  ...
)

```

Arguments

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from <code>{dplyr}</code> should be ungrouped before they are entered as data.
<code>x</code>	A numeric variable from the dataframe data.
<code>grouping.var</code>	A single grouping variable.
<code>binwidth</code>	The width of the histogram bins. Can be specified as a numeric value, or a function that calculates width from <code>x</code> . The default is to use the $\max(x) - \min(x) / \sqrt{N}$. You should always check this value and explore multiple widths to find the best to illustrate the stories in your data.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>plotgrid.args</code>	A list of additional arguments passed to <code>patchwork::wrap_plots</code> , except for <code>guides</code> argument which is already separately specified here.

annotation.args

A list of additional arguments passed to patchwork::plot_annotation.

...

Arguments passed on to gghistostats

normal.curve A logical value that decides whether to super-impose a normal curve using stats::dnorm(mean(x), sd(x)). Default is FALSE.

normal.curve.args A list of additional aesthetic arguments to be passed to the normal curve.

bin.args A list of additional aesthetic arguments to be passed to the stat_bin used to display the bins. Do not specify binwidth argument in this list since it has already been specified using the dedicated argument.

centrality.line.args A list of additional aesthetic arguments to be passed to the geom_line used to display the lines corresponding to the centrality parameter.

type A character specifying the type of statistical approach:

- "parametric"
- "nonparametric"
- "robust"
- "bayes"

You can specify just the initial letter.

test.value A number indicating the true value of the mean (Default: 0).

k Number of digits after decimal point (should be an integer) (Default: k = 2L).

conf.level Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).

tr Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of tr, which is by default set to 0.2. Lowering the value might help.

bf.prior A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, sqrt(2)/2, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.

effsize.type Type of effect size needed for *parametric* tests. The argument can be "d" (for Cohen's d) or "g" (for Hedge's g).

xlab Label for x axis variable. If NULL (default), variable name for x will be used.

bf.message Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).

results.subtitle Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.

subtitle The text for the plot subtitle. Will work only if results.subtitle = FALSE.

caption The text for the plot caption. This argument is relevant only if bf.message = FALSE.

`centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument.

- **mean** for parametric statistics
- **median** for non-parametric statistics
- **trimmed mean** for robust statistics
- **MAP estimator** for Bayesian statistics

If you want default centrality parameter, you can specify this using `centrality.type` argument.

`centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as type argument. You can specify this to be:

- "parametric" (for **mean**)
- "nonparametric" (for **median**)
- robust (for **trimmed mean**)
- bayes (for **MAP estimator**)

Just as type argument, abbreviations are also accepted.

`ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

`ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`.

Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/gghistostats.html

See Also

[gghistostats](#), [ggdotplotstats](#), [grouped_ggdotplotstats](#)

Examples

```
# for reproducibility
set.seed(123)
library(ggstatsplot)

# plot
```

```
grouped_gghistostats(
  data          = iris,
  x             = Sepal.Length,
  test.value    = 5,
  grouping.var  = Species,
  plotgrid.args = list(nrow = 1),
  annotation.args = list(tag_levels = "i")
)
```

grouped_ggpiestats *Grouped pie charts with statistical tests*

Description

Helper function for `ggstatsplot::ggpiestats` to apply this function across multiple levels of a given factor and combining the resulting plots using `ggstatsplot::combine_plots`.

Usage

```
grouped_ggpiestats(
  data,
  ...,
  grouping.var,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list()
)
```

Arguments

<code>data</code>	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from <code>{dplyr}</code> should be ungrouped before they are entered as data.
<code>...</code>	Arguments passed on to ggpiestats
<code>x</code>	The variable to use as the rows in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped.
<code>y</code>	The variable to use as the columns in the contingency table. Please note that if there are empty factor levels in your variable, they will be dropped. Default is NULL. If NULL, one-sample proportion test (a goodness of fit test) will be run for the x variable. Otherwise an appropriate association test will be run. This argument can not be NULL for <code>ggbarstats</code> function.
<code>proportion.test</code>	Decides whether proportion test for x variable is to be carried out for each level of y. Defaults to <code>results.subtitle</code> . In <code>ggbarstats</code> , only <i>p</i> -values from this test will be displayed.

- `perc.k` Numeric that decides number of decimal places for percentage labels (Default: 0L).
- `label` Character decides what information needs to be displayed on the label in each pie slice. Possible options are "percentage" (default), "counts", "both".
- `label.args` Additional aesthetic arguments that will be passed to `geom_label`.
- `label.repel` Whether labels should be repelled using `ggrepel` package. This can be helpful in case the labels are overlapping.
- `legend.title` Title text for the legend.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
- `ggplot.component` A `ggplot` component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.
- `package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.
- `ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`. Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.
- `type` A character specifying the type of statistical approach:
- "parametric"
 - "nonparametric"
 - "robust"
 - "bayes"
- You can specify just the initial letter.
- `k` Number of digits after decimal point (should be an integer) (Default: `k = 2L`).
- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `paired` Logical indicating whether data came from a within-subjects or repeated measures design study (Default: FALSE). If TRUE, McNemar's test

	expression will be returned. If FALSE, Pearson's chi-square test will be returned.
	counts The variable in data containing counts, or NULL if each row represents a single observation.
	ratio A vector of proportions: the expected proportions for the proportion test (should sum to 1). Default is NULL, which means the null is equal theoretical proportions across the levels of the nominal variable. This means if there are two levels this will be <code>ratio = c(0.5, 0.5)</code> or if there are four levels this will be <code>ratio = c(0.25, 0.25, 0.25, 0.25)</code> , etc.
	sampling.plan Character describing the sampling plan. Possible options are "indepMulti" (independent multinomial; default), "poisson", "jointMulti" (joint multinomial), "hypergeom" (hypergeometric). For more, see <code>?BayesFactor::contingencyTable</code> .
	fixed.margin For the independent multinomial sampling plan, which margin is fixed ("rows" or "cols"). Defaults to "rows".
	prior.concentration Specifies the prior concentration parameter, set to 1 by default. It indexes the expected deviation from the null hypothesis under the alternative, and corresponds to Gunel and Dickey's (1974) "a" parameter.
grouping.var	A single grouping variable.
output	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
plotgrid.args	A list of additional arguments passed to <code>patchwork::wrap_plots</code> , except for <code>guides</code> argument which is already separately specified here.
annotation.args	A list of additional arguments passed to <code>patchwork::plot_annotation</code> .

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggpiestats.html

See Also

[ggbarstats](#), [ggpiestats](#), [grouped_ggbarstats](#)

Examples

```
set.seed(123)
library(ggstatsplot)

# grouped one-sample proportion test
grouped_ggpiestats(mtcars, x = cyl, grouping.var = am)
```

 grouped_ggscatterstats

Scatterplot with marginal distributions for all levels of a grouping variable

Description

Grouped scatterplots from {ggplot2} combined with marginal distribution plots with statistical details added as a subtitle.

Usage

```
grouped_ggscatterstats(
  data,
  ...,
  grouping.var,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list()
)
```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
...	Arguments passed on to ggscatterstats
label.var	Variable to use for points labels entered as a symbol (e.g. var1).
label.expression	An expression evaluating to a logical vector that determines the subset of data points to label (e.g. <code>y < 4 & z < 20</code>). While using this argument with <code>purrr::pmap</code> , you will have to provide a quoted expression (e.g. <code>quote(y < 4 & z < 20)</code>).
point.label.args	A list of additional aesthetic arguments to be passed to <code>ggrepel::geom_label_repel</code> geom used to display the labels.
smooth.line.args	A list of additional aesthetic arguments to be passed to <code>geom_smooth</code> geom used to display the regression line.
point.args	A list of additional aesthetic arguments to be passed to <code>geom_point</code> geom used to display the raw data points.
marginal	Decides whether marginal distributions will be plotted on axes using <code>ggside</code> functions. The default is TRUE. The package <code>ggside</code> must already be installed by the user.
point.width.jitter, point.height.jitter	Degree of jitter in x and y direction, respectively. Defaults to 0 (0%) of the resolution of the data. Note that the jitter should not be specified in the <code>point.args</code> because this information will be passed to two different geoms: one displaying the points and the other displaying the *labels for these points.

- `xfill,yfill` Character describing color fill for x and y axes marginal distributions (default: "#009E73" (for x) and "#D55E00" (for y)). Note that the defaults are colorblind-friendly.
- `xsidehistogram.args,ysidehistogram.args` A list of arguments passed to respective `geom_s` from `ggside` package to change the marginal distribution histograms plots.
- `x` The column in data containing the explanatory variable to be plotted on the x-axis.
- `y` The column in data containing the response (outcome) variable to be plotted on the y-axis.
- `type` A character specifying the type of statistical approach:
- "parametric"
 - "nonparametric"
 - "robust"
 - "bayes"
- You can specify just the initial letter.
- `k` Number of digits after decimal point (should be an integer) (Default: $k = 2L$).
- `conf.level` Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
- `tr` Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of `tr`, which is by default set to 0.2. Lowering the value might help.
- `bf.prior` A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to r scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
- `xlab` Label for x axis variable. If NULL (default), variable name for x will be used.
- `ylab` Labels for y axis variable. If NULL (default), variable name for y will be used.
- `bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).
- `results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.
- `subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.
- `caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.
- `ggplot.component` A `ggplot` component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for `grouped_` variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

<code>ggtheme</code>	A {ggplot2} theme. Default value is <code>ggstatsplot::theme_ggstatsplot()</code> . Any of the {ggplot2} themes (e.g., <code>theme_bw()</code>), or themes from extension packages are allowed (e.g., <code>ggthemes::theme_fivethirtyeight()</code> , <code>hrbrthemes::theme_ipsum_ps()</code> , etc.). But note that sometimes these themes will remove some of the details that {ggstatsplot} plots typically contains. For example, if relevant, <code>ggbetweenstats()</code> shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. <code>ggthemes::theme_fivethirtyeight()</code>) will remove the secondary Y-axis and thus the details as well.
<code>grouping.var</code>	A single grouping variable.
<code>output</code>	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
<code>plotgrid.args</code>	A list of additional arguments passed to <code>patchwork::wrap_plots</code> , except for <code>guides</code> argument which is already separately specified here.
<code>annotation.args</code>	A list of additional arguments passed to <code>patchwork::plot_annotation</code> .

Details

For details, see: https://indrajeetpatil.github.io/ggstatsplot/articles/web_only/ggscatterstats.html

See Also

[ggscatterstats](#), [ggcorrmat](#), [grouped_ggcorrmat](#)

Examples

```
# to ensure reproducibility
set.seed(123)
library(ggstatsplot)
library(dplyr, warn.conflicts = FALSE)
library(ggplot2)

# basic function call
grouped_ggscatterstats(
  data      = filter(movies_long, genre == "Comedy" | genre == "Drama"),
  x         = length,
  y         = rating,
  type     = "robust",
  grouping.var = genre,
  ggplot.component = list(geom_rug(sides = "b"))
)

# using labeling
# (also show how to modify basic plot from within function call)
```

```

grouped_ggscatterstats(
  data          = filter(ggplot2::mpg, cyl != 5),
  x             = displ,
  y            = hwy,
  grouping.var  = cyl,
  type         = "robust",
  label.var     = manufacturer,
  label.expression = hwy > 25 & displ > 2.5,
  ggplot.component = scale_y_continuous(sec.axis = dup_axis())
)

# labeling without expression
grouped_ggscatterstats(
  data          = filter(movies_long, rating == 7, genre %in% c("Drama", "Comedy")),
  x            = budget,
  y           = length,
  grouping.var  = genre,
  bf.message   = FALSE,
  label.var    = "title",
  annotation.args = list(tag_levels = "a")
)

```

grouped_ggwithinstats *Violin plots for group or condition comparisons in within-subjects designs repeated across all levels of a grouping variable.*

Description

A combined plot of comparison plot created for levels of a grouping variable.

Usage

```

grouped_ggwithinstats(
  data,
  ...,
  grouping.var,
  output = "plot",
  plotgrid.args = list(),
  annotation.args = list()
)

```

Arguments

data	A data frame (or a tibble) from which variables specified are to be taken. Other data types (e.g., matrix, table, array, etc.) will not be accepted. Additionally, grouped data frames from {dplyr} should be ungrouped before they are entered as data.
...	Arguments passed on to ggwithinstats

`point.path,centrality.path` Logical that decides whether individual data points and means, respectively, should be connected using `geom_path`. Both default to TRUE. Note that `point.path` argument is relevant only when there are two groups (i.e., in case of a *t*-test). In case of large number of data points, it is advisable to set `point.path = FALSE` as these lines can overwhelm the plot.

`centrality.path.args,point.path.args` A list of additional aesthetic arguments passed on to `geom_path` connecting raw data points and mean points.

`boxplot.args` A list of additional aesthetic arguments passed on to `geom_boxplot`.

`xlab` Label for x axis variable. If NULL (default), variable name for x will be used.

`ylab` Labels for y axis variable. If NULL (default), variable name for y will be used.

`pairwise.comparisons` Logical that decides whether pairwise comparisons are to be displayed (default: TRUE). Please note that only **significant** comparisons will be shown by default. To change this behavior, select appropriate option with `pairwise.display` argument. The pairwise comparison dataframes are prepared using the `pairwise_comparisons` function. For more details about pairwise comparisons, see the documentation for that function.

`p.adjust.method` Adjustment method for *p*-values for multiple comparisons. Possible methods are: "holm" (default), "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none".

`pairwise.display` Decides *which* pairwise comparisons to display. Available options are:

- "significant" (abbreviation accepted: "s")
- "non-significant" (abbreviation accepted: "ns")
- "all"

You can use this argument to make sure that your plot is not uber-cluttered when you have multiple groups being compared and scores of pairwise comparisons being displayed.

`bf.message` Logical that decides whether to display Bayes Factor in favor of the *null* hypothesis. This argument is relevant only **for parametric test** (Default: TRUE).

`results.subtitle` Decides whether the results of statistical tests are to be displayed as a subtitle (Default: TRUE). If set to FALSE, only the plot will be returned.

`subtitle` The text for the plot subtitle. Will work only if `results.subtitle = FALSE`.

`caption` The text for the plot caption. This argument is relevant only if `bf.message = FALSE`.

`outlier.tagging` Decides whether outliers should be tagged (Default: FALSE).

`outlier.label` Label to put on the outliers that have been tagged. This **can't** be the same as x argument.

`outlier.label.args` A list of additional aesthetic arguments to be passed to `ggrepel::geom_label_repel` for outlier label plotting.

`outlier.coef` Coefficient for outlier detection using Tukey's method. With Tukey's method, outliers are below (1st Quartile) or above (3rd Quartile) `outlier.coef` times the Inter-Quartile Range (IQR) (Default: 1.5).

`centrality.plotting` Logical that decides whether centrality tendency measure is to be displayed as a point with a label (Default: TRUE). Function decides which central tendency measure to show depending on the type argument.

- **mean** for parametric statistics
- **median** for non-parametric statistics
- **trimmed mean** for robust statistics
- **MAP estimator** for Bayesian statistics

If you want default centrality parameter, you can specify this using `centrality.type` argument.

`centrality.type` Decides which centrality parameter is to be displayed. The default is to choose the same as type argument. You can specify this to be:

- "parameteric" (for **mean**)
- "nonparametric" (for **median**)
- robust (for **trimmed mean**)
- bayes (for **MAP estimator**)

Just as type argument, abbreviations are also accepted.

`point.args` A list of additional aesthetic arguments to be passed to the `geom_point` displaying the raw data.

`violin.args` A list of additional aesthetic arguments to be passed to the `geom_violin`.

`ggplot.component` A ggplot component to be added to the plot prepared by `{ggstatsplot}`. This argument is primarily helpful for grouped_ variants of all primary functions. Default is NULL. The argument should be entered as a `{ggplot2}` function or a list of `{ggplot2}` functions.

`package,palette` Name of the package from which the given palette is to be extracted. The available palettes and packages can be checked by running `View(paletteer::palettes_d_names)`.

`centrality.point.args,centrality.label.args` A list of additional aesthetic arguments to be passed to `geom_point` and `ggrepel::geom_label_repel` geoms, which are involved in mean plotting.

`ggsignif.args` A list of additional aesthetic arguments to be passed to `ggsignif::geom_signif`.

`ggtheme` A `{ggplot2}` theme. Default value is `ggstatsplot::theme_ggstatsplot()`.

Any of the `{ggplot2}` themes (e.g., `theme_bw()`), or themes from extension packages are allowed (e.g., `ggthemes::theme_fivethirtyeight()`, `hrbrthemes::theme_ipsum_ps()`, etc.). But note that sometimes these themes will remove some of the details that `{ggstatsplot}` plots typically contains. For example, if relevant, `ggbetweenstats()` shows details about multiple comparison test as a label on the secondary Y-axis. Some themes (e.g. `ggthemes::theme_fivethirtyeight()`) will remove the secondary Y-axis and thus the details as well.

x	The grouping (or independent) variable from data. In case of a repeated measures or within-subjects design, if <code>subject.id</code> argument is not available or not explicitly specified, the function assumes that the data has already been sorted by such an id by the user and creates an internal identifier. So if your data is not sorted, the results <i>can</i> be inaccurate when there are more than two levels in x and there are NAs present. The data is expected to be sorted by user in subject-1,subject-2, ..., pattern.
y	The response (or outcome or dependent) variable from data.
type	A character specifying the type of statistical approach: <ul style="list-style-type: none"> • "parametric" • "nonparametric" • "robust" • "bayes" <p>You can specify just the initial letter.</p>
k	Number of digits after decimal point (should be an integer) (Default: $k = 2L$).
conf.level	Scalar between 0 and 1. If unspecified, the defaults return 95% confidence/credible intervals (0.95).
effsize.type	Type of effect size needed for <i>parametric</i> tests. The argument can be "eta" (partial eta-squared) or "omega" (partial omega-squared).
bf.prior	A number between 0.5 and 2 (default 0.707), the prior width to use in calculating Bayes factors and posterior estimates. In addition to numeric arguments, several named values are also recognized: "medium", "wide", and "ultrawide", corresponding to <i>r</i> scale values of 1/2, $\sqrt{2}/2$, and 1, respectively. In case of an ANOVA, this value corresponds to scale for fixed effects.
tr	Trim level for the mean when carrying out robust tests. In case of an error, try reducing the value of <code>tr</code> , which is by default set to 0.2. Lowering the value might help.
nboot	Number of bootstrap samples for computing confidence interval for the effect size (Default: $100L$).
grouping.var	A single grouping variable.
output	Character that describes what is to be returned: can be "plot" (default) or "subtitle" or "caption". Setting this to "subtitle" will return the expression containing statistical results. If you have set <code>results.subtitle = FALSE</code> , then this will return a NULL. Setting this to "caption" will return the expression containing details about Bayes Factor analysis, but valid only when <code>type = "parametric"</code> and <code>bf.message = TRUE</code> , otherwise this will return a NULL.
plotgrid.args	A list of additional arguments passed to <code>patchwork::wrap_plots</code> , except for <code>guides</code> argument which is already separately specified here.
annotation.args	A list of additional arguments passed to <code>patchwork::plot_annotation</code> .

See Also

[ggwithinstats](#), [ggbetweenstats](#), [grouped_ggbetweenstats](#)

Examples

```

if (require("PMCMRplus")) {
  # to get reproducible results from bootstrapping
  set.seed(123)
  library(ggstatsplot)
  library(dplyr, warn.conflicts = FALSE)
  library(ggplot2)

  # the most basic function call
  grouped_ggwithinstats(
    data      = filter(bugs_long, condition %in% c("HDHF", "HDLF")),
    x         = condition,
    y         = desire,
    grouping.var = gender,
    type      = "np", # non-parametric test
    # additional modifications for **each** plot using `{ggplot2}` functions
    ggplot.component = scale_y_continuous(breaks = seq(0, 10, 1), limits = c(0, 10))
  )
}

```

iris_long

Edgar Anderson's Iris Data in long format.

Description

Edgar Anderson's Iris Data in long format.

Usage

```
iris_long
```

Format

A data frame with 600 rows and 5 variables

- `id`. Dummy identity number for each flower (150 flowers in total).
- `Species`. The species are *Iris setosa*, *versicolor*, and *virginica*.
- `condition`. Factor giving a detailed description of the attribute (Four levels: "Petal.Length", "Petal.Width", "Sepal.Length", "Sepal.Width").
- `attribute`. What attribute is being measured ("Sepal" or "Pepal").
- `measure`. What aspect of the attribute is being measured ("Length" or "Width").
- `value`. Value of the measurement.

Details

This famous (Fisher's or Anderson's) iris data set gives the measurements in centimeters of the variables sepal length and width and petal length and width, respectively, for 50 flowers from each of 3 species of iris. The species are *Iris setosa*, *versicolor*, and *virginica*.

This is a modified dataset from `datasets` package.

Examples

```
dim(iris_long)
head(iris_long)
dplyr::glimpse(iris_long)
```

<code>movies_long</code>	<i>Movie information and user ratings from IMDB.com (long format).</i>
--------------------------	--

Description

Movie information and user ratings from IMDB.com (long format).

Usage

```
movies_long
```

Format

A data frame with 1,579 rows and 8 variables

- `title`. Title of the movie.
- `year`. Year of release.
- `budget`. Total budget (if known) in US dollars
- `length`. Length in minutes.
- `rating`. Average IMDB user rating.
- `votes`. Number of IMDB users who rated this movie.
- `mpaa`. MPAA rating.
- `genre`. Different genres of movies (action, animation, comedy, drama, documentary, romance, short).

Details

Modified dataset from `ggplot2movies` package.

The internet movie database, <https://imdb.com/>, is a website devoted to collecting movie data supplied by studios and fans. It claims to be the biggest movie database on the web and is run by amazon.

Source

<https://CRAN.R-project.org/package=ggplot2movies>

Examples

```
dim(movies_long)
head(movies_long)
dplyr::glimpse(movies_long)
```

theme_ggstatsplot	<i>Default theme used in {ggstatsplot}</i>
-------------------	--

Description

Common theme used across all plots generated in {ggstatsplot} and *assumed* by the author to be aesthetically pleasing to the user/reader. The theme is a wrapper around theme_bw().

All {ggstatsplot} functions have a ggtheme parameter that let you choose a different theme.

Usage

```
theme_ggstatsplot()
```

Value

A ggplot object with the theme_ggstatsplot theme overlaid.

Examples

```
library(ggplot2)
library(ggstatsplot)

ggplot(mtcars, aes(wt, mpg)) +
  geom_point() +
  theme_ggstatsplot()
```

Titanic_full	<i>Titanic dataset.</i>
--------------	-------------------------

Description

Titanic dataset.

Usage

```
Titanic_full
```

Format

A data frame with 2201 rows and 5 variables

- `id`. Dummy identity number for each person.
- `Class`. 1st, 2nd, 3rd, Crew.
- `Sex`. Male, Female.
- `Age`. Child, Adult.
- `Survived`. No, Yes.

Details

This data set provides information on the fate of passengers on the fatal maiden voyage of the ocean liner 'Titanic', summarized according to economic status (class), sex, age and survival.

This is a modified dataset from `datasets` package.

Examples

```
dim(Titanic_full)
head(Titanic_full)
dplyr::glimpse(Titanic_full)
```

Index

- * **datasets**
 - bugs_long, 4
 - bugs_wide, 5
 - iris_long, 68
 - movies_long, 69
 - Titanic_full, 70
- _PACKAGE (ggstatsplot-package), 3
- bugs_long, 4
- bugs_wide, 5
- combine_plots, 6
- extract_stats, 7
- ggbarstats, 8, 32, 42, 44, 60
- ggbetweenstats, 12, 40, 45, 48, 67
- ggcoefstats, 17
- ggcorrmat, 20, 36, 49, 51, 63
- ggdotplotstats, 23, 29, 52, 54, 57
- gghistostats, 26, 26, 54, 56, 57
- ggpiestats, 11, 29, 44, 58, 60
- ggscatterstats, 22, 33, 51, 61, 63
- ggstatsplot (ggstatsplot-package), 3
- ggstatsplot-package, 3
- ggwithinstats, 16, 36, 48, 64, 67
- grouped_ggbarstats, 11, 32, 41, 60
- grouped_ggbetweenstats, 16, 40, 44, 67
- grouped_ggcorrmat, 22, 36, 49, 63
- grouped_ggdotplotstats, 26, 29, 52, 57
- grouped_gghistostats, 26, 29, 54, 55
- grouped_ggpiestats, 11, 32, 44, 58
- grouped_ggscatterstats, 22, 36, 51, 61
- grouped_ggwithinstats, 16, 40, 48, 64
- iris_long, 68
- movies_long, 69
- theme(legend.position=...), 6
- theme_ggstatsplot, 70
- Titanic_full, 70