

Package ‘lotri’

January 5, 2021

Title A Simple Way to Specify Symmetric, Block Diagonal Matrices

Version 0.3.1

Maintainer Matthew L. Fidler <matthew.fidler@gmail.com>

Description Provides a simple mechanism to specify a symmetric block diagonal matrices (often used for covariance matrices). This is based on the domain specific language implemented in 'nlmixr' but expanded to create matrices in R generally instead of specifying parts of matrices to estimate.

Depends R (>= 3.4.0)

License GPL (>= 2)

Encoding UTF-8

LazyData true

Imports methods, utils, stats

Suggests testthat, covr, knitr, rmarkdown, Matrix, microbenchmark, ggplot2

NeedsCompilation yes

Biarch true

RoxygenNote 7.1.1

VignetteBuilder knitr

BugReports <https://github.com/nlmixrdevelopment/lotri/issues>

URL <https://github.com/nlmixrdevelopment/lotri>

Author Matthew L. Fidler [aut, cre] (<<https://orcid.org/0000-0001-8538-6691>>)

Repository CRAN

Date/Publication 2021-01-05 15:50:05 UTC

R topics documented:

as.lotri	2
lotri	2
lotriMat	4
lotriSep	6

Index**8**

as.lotri	<i>As lower triangular matrix</i>
----------	-----------------------------------

Description

As lower triangular matrix

Usage

```
as.lotri(x, ..., default = "")

## S3 method for class 'matrix'
as.lotri(x, ..., default = "")

## Default S3 method:
as.lotri(x, ..., default = "")
```

Arguments

x	Matrix or other data frame
...	Other factors
default	Is the default factor when no conditioning is implemented.

Value

Lower triangular matrix

Author(s)

Matthew Fidler

lotri	<i>Easily Specify block-diagonal matrices with lower triangular info</i>
-------	--

Description

Easily Specify block-diagonal matrices with lower triangular info

Usage

```
lotri(x, ..., envir = parent.frame())
```

Arguments

x	list, matrix or expression, see details
...	Other arguments treated as a list that will be concatenated then reapplied to this function.
envir	the environment in which expr is to be evaluated. May also be NULL, a list, a data frame, a pairlist or an integer as specified to sys.call .

Details

This can take an R matrix, a list including matrices or expressions, or expressions

Expressions can take the form

name ~ estimate

Or the lower triangular matrix when "adding" the names

name1 + name2 ~ c(est1, est2, est3)

The matrices are concatenated into a block diagonal matrix, like [bdiag](#), but allows expressions to specify matrices easier.

Value

named symmetric matrix useful in RxODE simulations (and perhaps elsewhere)

Author(s)

Matthew L Fidler

Examples

```
## A few ways to specify the same matrix
lotri({et2 + et3 + et4 ~ c(40,
                          0.1, 20,
                          0.1, 0.1, 30)})
```

```
## You do not need to enclose in {}
lotri(et2 + et3 + et4 ~ c(40,
                          0.1, 20,
                          0.1, 0.1, 30),
      et5 ~ 6)
```

```
## But if you do enclose in {}, you can use
## multi-line matrix specifications:
```

```
lotri({et2 + et3 + et4 ~ c(40,
                          0.1, 20,
                          0.1, 0.1, 30)
      et5 ~ 6
    })
```

```
## You can also add lists or actual R matrices as in this example:
```

```

lotri(list(et2 + et3 + et4 ~ c(40,
                             0.1, 20,
                             0.1, 0.1, 30),
         matrix(1,dimnames=list("et5","et5"))))

## Overall this is a flexible way to specify symmetric block
## diagonal matrices.

## For RxODE, you may also condition based on different levels of
## nesting with lotri; Here is an example:

mat <- lotri(lotri(iov.Ka ~ 0.5,
                  iov.Cl ~ 0.6),
            lotri(occ.Ka ~ 0.5,
                  occ.Cl ~ 0.6) | occ(lower=4,nu=3))

mat

## you may access features of the matrix simply by `$` that is

mat$lower # Shows the lower bound for each condition

mat$lower$occ # shows the lower bound for the occasion variable

## Note that `lower` fills in defaults for parameters. This is true
## for `upper` true; In fact when accessing this the defaults
## are put into the list

mat$upper

## However all other values return NULL if they are not present like

mat$lotri

## And values that are specified once are only returned on one list:

mat$nu

mat$nu$occ
mat$nu$id

## You can also change the default condition with `as.lotri`

mat <- as.lotri(mat,default="id")

mat

```

Description

This creates a named banded symmetric matrix from a list of named symmetric matrices.

Usage

```
lotriMat(matList, format = NULL, start = 1L)
```

Arguments

matList	list of symmetric named matrices
format	The format of dimension names when a sub-matrix is repeated. The format will be called with the dimension number, so "ETA[%d]" would represent "ETA[1]", "ETA[2]", etc
start	The number the counter of each repeated dimension should start.

Value

Named symmetric block diagonal matrix based on concatenating the list of matrices together

Author(s)

Matthew Fidler

Examples

```
testList <- list(lotri({et2 + et3 + et4 ~ c(40,
                                0.1, 20,
                                0.1, 0.1, 30)}),
                lotri(et5 ~ 6))

testList

lotriMat(testList)

# Another option is to repeat a matrix a number of times. This
# can be done with list(matrix, # times to repeat).

# In the example below, the first matrix is repeated 3 times
testList <- list(list(lotri({et2 + et3 + et4 ~ c(40,
                                0.1, 20,
                                0.1, 0.1, 30)}), 3),
                lotri(et5 ~ 6))

lotriMat(testList)

# Notice that the dimension names `et2`, `et3` and `et4` are
# repeated.

# Another option is to name the dimensions. For example it could
```

```
# be `ETA[1]`, `ETA[2]`, etc by using the 'format' option:
lotriMat(testList, "ETA[%d]")

# Or could start with ETA[2]:
lotriMat(testList, "ETA[%d]", 2)
```

lotriSep

Separate a lotri matrix into above and below lotri matrices

Description

This is used for creating nesting simulations in 'RxODE' and may not be useful for external function calls.

Usage

```
lotriSep(x, above, below, aboveStart = 1L, belowStart = 1L)
```

Arguments

x	lotri matrix
above	Named integer vector listing variability above the id level. Each element lists the number of population differences in the whole data-set (as integer)
below	Named integer vector listing variability below the id level. Each element lists the number of items below the individual level. For example with 3 occasions per individual you could use 'c(occ=3L)'
aboveStart	Add the attribute of where THETA[#] will be added
belowStart	Add the attribute of where ETA[#] will be added

Value

List of two lotri matrices

Author(s)

Matthew Fidler

Examples

```
omega <- lotri(lotri(eta.Cl ~ 0.1,
                   eta.Ka ~ 0.1) | id(nu=100),
              lotri(eye.Cl ~ 0.05,
                   eye.Ka ~ 0.05) | eye(nu=50),
              lotri(iov.Cl ~ 0.01,
                   iov.Ka ~ 0.01) | occ(nu=200),
```

```
lotri(inv.Cl ~ 0.02,  
      inv.Ka ~ 0.02) | inv(nu=10)
```

```
lotriSep(omega, above=c(inv=10L), below=c(eye=2L, occ=4L))
```

Index

`as.lotri`, 2

`bdiag`, 3

`environment`, 3

`lotri`, 2

`lotriMat`, 4

`lotriSep`, 6

`sys.call`, 3